



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[34560-584](#)

[34560-584.](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt














FR

Cette fiche technique est
présentée par le fabricant

Subracks - *europac*PRO ServicePLUS

Rear horizontal rails, top and bottom

Order Information

 <p>With HP markings from 28 HP, Al extrusion, anodised finish, conductive surface</p>		For indirect backplane mounting with insulation strip		For direct backplane mounting		For direct fixing of connectors in accordance with EN 60603-2 (DIN 41612)	
		 <p>06197011</p> <p>"light" Type L-ST standard</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>	 <p>06197011</p> <p>"heavy" Type H-ST standard</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>	 <p>06197011</p> <p>"light" Type L-VT + 3 mm</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>	 <p>06197011</p> <p>"heavy" Type H-VT + 3 mm</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>	 <p>06197011</p> <p>"light" Type L-MZ with Z-rail</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>	 <p>06197011</p> <p>"heavy" Type H-MZ with Z-rail</p>  <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p> <p>1 piece (SPQ 10)¹⁾</p>
Usable length HP	Length mm	34560-420	34560-520	34560-620	34560-720	34560-820	34560-920
20	106.68	34560-428	34560-528	34560-628	34560-728	34560-828	34560-928
28	147.32	34560-440	34560-540	34560-640	34560-740	34560-840	34560-940
40	208.28	34560-442	34560-542	34560-642	34560-742	34560-842	34560-942
42	218.44	34560-463	34560-563	34560-663	34560-763	34560-863	34560-963
63	325.12	34560-484	34560-584	34560-684	34560-784	34560-884	34560-984
84	431.80	34560-401	34560-501	34560-601	34560-701	34560-801	–
–	1000						
Screw, M4 x 14, PU 100 pieces, for fastening horizontal rail to side panel		24560-130	24560-130	24560-130	24560-130	24560-130	24560-130
Screw, M4 x 10, required if guide rails are screwed to slot 1, PU 100 pieces		–	24560-155	–	24560-155	–	24560-155
Perforated rail for connector mounting with insulation strip see page		6.34	6.34	–	–	–	–
Z-rail for connector mounting without insulation strip see page		6.34	6.34	–	–	–	–
Insulation strips see page		6.33	6.33	–	–	–	–
Threaded inserts see page		6.33	6.33	6.33	6.33	6.33	6.33

¹⁾ SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ);

please order at least the SPQ quantity or a multiple

"light": loading capacity up to approx. 7.5 kg; "heavy": loading capacity > 7.5 kg

Note

- 1000 mm version without M4 thread to front, without printed markings and without notch for 19"-bracket
- Rugged horizontal rails with 3 fixing holes see section "Rugged Subracks"



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[34560-584](#)

[34560-584.](#)

EN

This Datasheet is presented by
the manufacturer

DE

Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR

Cette fiche technique est
présentée par le fabricant