note:

default value 5.



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Yes*: Joystick support to control PTZ speed in Crystal

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks			
SNB-1000	v1.07_11040 7	H.264 MPEG4 M-JPEG	1	640x480	1-way	1/1	-	Yes	-	Yes				
Note:	This is POE ca	his is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.												
Note:	I/O and MD is discontinued.	/O and MD is unstable, which is a known issue reported by Samsung. They won't do any change since the camera is liscontinued.												
SNB-1001	1.00_111226	H.264 M-JPEG	1	640x480	1-way	1/0	-	Yes	-	Yes	Test by link			
SNB-2000		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	-	Supported by design			
SNB-3000		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	-	Supported by design			
SNB-3002	refer to SND- 3082/F (FW 2.10_130416	H.264 MPEG4 M-JPEG	1	704x576(PA L) 704x480(NT SC)	1-way	1/1	-	Yes	Yes	yes	Supported by design			
SNB-5000	v1.33_11021 8	H.264 MPEG4 M-JPEG	1	1280×1024	1-way	1/1	-	Yes	-	Yes				
SNB-5000A	refer to SND5080 (FW 3.10_130416)	H.264 MPEG4	1	1280×1024	1-way	1/1	-	Yes	Yes	-	Supported by design			
SNB-5001	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	-	Yes	-	Yes				
SNB-5003	1.12_131031	H.264 M-JPEG	1	1280x1024	*2	*2	*2	Yes	-	Yes	Test by link			
SNB-5004	1.12_131031	H.264 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes				
	For CNR FOO3	CND FOO	4 CND	EU03 CND E	004 and CNI	/ 500/1								

For SNB-5003, SNB-5004, SND-5083, SND-5084 and SNV-5084:

1. Camera can support 128 preset points, but we are only support 64 preset points.

2. Before starting "talk", we do check that the talk's gain is greater than zero. If it is 0, we are going to adjust gain to

3. If user do change audio setting in the website, then the previous connection will be interrupted and re-connect.



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks
SNB-6003	refer to SND- 6083(FW 1.00_130412	H264 MJPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes	Supported by design
SNB-6004		H264 MJPEG	1	1920×1080	*2	*2	Yes	Yes	*2	Yes*	Supported by design
SND-6011R	1.11_131011	H.264 M-JPEG	1	1920×1080	-	*2	ı	Yes	-	Yes*	
SNB-7000	Refer to SND-7080	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	-	Yes	Supported by design
SNB-7001	Refer to SND-7011	H.264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	Yes	Supported by design
SNB-7002	1.06_130402	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	Yes	
note:	Sometimes ca	n't get cor	rect UI	setting becaus	e camera re	esponse t	ime to	o long.			
SNC-B2315	2.01	MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	-	
SNC-B2331	v1.00_09081 0	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	-	
SNC-B2335	v1.10_10012 9	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	-	
SNC-B5368	v1.00_09100 1	H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	Yes	-	-	
SNC-B5395	2.10	MPEG4 M-JPEG	1	720x576	1-way	2/2	-	Yes	-	-	
SNC-B5399	v1.10_09112 0	H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	1	Yes	-	-	
SNC-C6225	1.01	MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	-	-	
SNC-C7225	1.01	MPEG4 M-JPEG	1	720x576	1-way	2/1	Yes	Yes	-	-	Supported by design



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks
SNC-C7478	v1.01_09062 5	MPEG4 M-JPEG	1	720x576	1-way	8/4	Yes	Yes	-	-	
SNC-M300	v2.11_09072 9	MPEG4 M-JPEG	1	2048x1536	1-way	2/2	-	Yes	-	-	
SND-1010	v1.07_11040 7	H.264 MPEG4 M-JPEG	1	640x480	-	1/1	-	Yes	-	Yes	
Note:	This is POE camera, but the device is unstable without AC power connection. We suggest connecting with AC power.										
Note:	I/O and MD is discontinued.	unstable,	which is	a known issu	e reported	oy Samsı	ıng. Th	iey won't d	o any chai	nge since the	e camera is
SND-1011	1.00_111226	H.264 M-JPEG	1	640x480	-	1/0	-	Yes	-	Yes	Test by link
SND-1080	1.00_111226	H.264 M-JPEG	1	640x480	1-way	1/0	-	Yes	-	Yes	Test by link
SND-3080		H.264 MPEG4 M-JPEG	1	720x576	-	2/2	-	-	-	-	Supported by design
SND-3082	Refer to SND- 3082/F(2.10_ 130416)	H.264 MPEG4 M-JPEG	1	704x576(PA L) 704x480(NT SC)	1-way	1/1	-	Yes	Yes	Yes	Supported by design
SND- 3082/F	2.10_130416	H.264 MPEG4 M-JPEG	1	704x576(PA L) 704x480(NT	1-way	1/1	ı	Yes	Yes	Yes	
SND-5010	1.00_120626	H.264 M-JPEG	1	1280*1024	ı	0/0	I	Yes	-	Yes	
SND-5011	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	ı	Yes	-	Yes	
SND-5061	1.00_120521	H.264 M-JPEG	1	1280x1024	-	1/0	-	Yes	-	Yes	
SND-5080	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
SND-5083	1.12_131031 refer to SNB- 5003	H.264 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes	
SND-5084	1.12_131031 refer to SNB- 5004	H.264 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes	



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

			C3 . JC	ystick suppe	or to conti	011123	pccu i	ii Ci yatai				
Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks	
SND-6083	1.00_130412	H264 MJPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes		
SND-6084	SNV-6084R- V3.01_14080 4	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	*2	Yes*		
Note:	1. The camera	with high	er quali	ty and resoluti	ion is unable	to achie	ve 30	fps (Camer	a perform	ance issue)	•	
SND-6084R	1.00_130316 refer to SNB- 6004	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	-	Yes	Supported by design	
SND-7011	1.00_120601	H.264 M-JPEG	1	2048x1536	-	1/0	-	Yes	-	Yes		
Note:	Sometimes ca	n't get cor	rect UI	setting becaus	se camera re	esponse t	ime to	o long.			•	
SND-7061	Refer to SND-7011	H.264 M-JPEG	1	2048x1536	-	1/1	-	Yes	-	Yes	Supported by design	
SND-7080	v1.10_11081 9	H.264 M-JPEG	1	2048x1536	1-way	1/1	ı	Yes	-	Yes		
SND-7082	1.00_120824	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes		Yes		
SND- 7082/F	refer to SNB- 7002 (1.06_13040 2)	H.264 M-JPEG	1	2048x1536	1-way	1/1	ı	Yes	Yes	Yes		
Note:	Sometimes ca	n't get cor	rect UI	setting becaus	se camera re	esponse t	ime to	o long.	<u>-</u>	-	-	
SND-7084	Refer to SND- 7084R(0.51_ 140116)	H.264	1	2048x1536	1-way	1/1	-	Yes	-	Yes*	Supported by design	
SND-7084R	0.51_140116	H.264	1	2048x1536	1-way	1/1	-	Yes	-	Yes*		
Note:	1.Snapshot's	resolution	will follo	w MJPEG stre	am. (Camer	a Firmwa	re issu	e)				
SNF-7010	1.00_130806	H264 MJPEG	1	2048x1536	1-way	-	-	Yes	-	Yes		
Note:	Fisheye came	ra	•	•	•	•		•	-	•	•	
SNF-8010N	1.00_140719	H.264 M-JPEG	1	2560x2048	*2	*2	-	*2	-	Yes*		
Note:	Firmware issu 2.To get OSD	The list of camera's stream 2 and stream 3 frame rate is not synchronized with the one on camerea's web.(Camera										



- : not avaliable on camera *1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks		
SNO-1080R	1.00_120125	H.264 M-JPEG	1	640x480	-	1/0	-	Yes	-	Yes	Test by link		
SNO-5080R	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes			
SNO-6011R	refer to SND- 6011R(1.11_ 131011)	H.264 M-JPEG	1	1920x1080	-	*2	-	Yes	*2	Yes*	Supported by design		
SNO- L6083R	1.00_150403	H.264 M-JPEG	1	1920x1080	*2	-	-	*2	-	Yes*			
Note:	1. Frame rate	. Frame rate list does not sync with web. (Camera Firmware issue)											
SNO-6084	refer to SND- 6083(1.00_1 30412)	H264 MJPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
SNO-6084R	1.00_130316 refer to SNB- 6004	H264 MJPEG	1	1920x1080	*2	*2	Yes	*2	-	Yes	Supported by design		
SNO-7080R	2.00_121004	H.264 MJPEG	1	2048x1536	*2	*2	Yes	Yes	-	Yes*	Test by link		
SNO-7082R	refer to SNB- 7002 (1.06_13040 2)	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
SNP-3120V	v1.24_11081 6	H.264 MPEG4 M-JPEG	1	704x480	1-way	2/2	Yes	Yes	-	Yes			
Note:	It takes a whil		after use	ers click stop p	atrol buttor	i.							
SNP-3301	v1.21_11031 0	H.264 MPEG4 M-JPEG	1	704x480	1-way	4/2	Yes	Yes	-	Yes			
SNP- 3302/H	Refer to SNP- 3371/H/TH	H.264 MPEG4 M-JPEG	1	704x480	1-way	4/2	Yes	Yes	-	Yes	Supported by design		
SNP-3370	v1.21_11031 0	H.264 MPEG4 M-JPEG	1	704x480	1-way	4/2	Yes	Yes	-	Yes			
Note:	SNP-3301/SN	P-3370: no	ot suppo	ort QCIF resolu	ıtion with H	.264 thro	ugh T0	CP.					
SNP- 3371/H/TH	S/W: 1.01_111104 ISP: 1.28	H.264 MPEG4 M-JPEG	1	704x480	1-way	4/2	Yes	Yes	-	Yes	Test by link		
SNP-3430H	v1.10_11081 8	H.264 MPEG4 M-JPEG	1	704x480	1-way	8/4	Yes	Yes	-	Yes			



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks		
Note:	This is POE ca	mera, but	the dev	ice is unstable	without AC	power c	onnect	ion. We sug	gest conr	necting with <i>i</i>	AC power.		
Note:	There is a can 1.11_11103		sue that	we cannot ge	t VBR/CBR	info to sh	now qu	ality or bit	rate corre	ctly. Please ι	ipgrade to FW		
Note:		oice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format.											
Note:	Not support A	lot support Area Zoom due to protocol limitation.											
Note:	The speed sele	ections of I	PTZ and	focus in Live\	/iew is not s	synchroni	zed wi	th camera v	web due to	protocol lin	nitation.		
SNP-5200H	v1.02_11060 3	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	4/2	-	Yes	-	Yes			
Note:	1. SNP-5200H is campatible with SNP-5200 2. Voice cracks in the video exported with ASF format, while the audio of video file is correctly recorded actually. Please choose to export with AVI format. 3. Not support Area Zoom due to protocol limitation. 4. The speed selections of PTZ and focus in LiveView is not synchronized with camera web due to protocol limitation.												
SNP-5300	1.10_130523	H.264 M-JPEG	1	1280x1024	*2	*2	Yes	Yes	Yes	Yes			
Note:	When main st	ream is MJ	PEG, du	al stream will	be H264. W	/hen maiı	n strea	m is H264,	dual strea	am will be M	IPEG		
SNP-6200	V1.00_12030 2	H.264 M-JPEG	1	1920×1080	1-way	4/2	Yes	Yes	-	Yes			
SNP-6200H	refer to SNP- 6200(FW V1.00_12030 2)	H.264 M-JPEG	1	1920x1080	1-way	4/2	Yes	Yes	-	Yes	Supported by design		
SNP- 6200HP	refer to SNP- 6200(FW V1.00_12030 2)	H.264 M-JPEG	1	1920x1080	1-way	4/2	Yes	Yes	-	Yes	Supported by design		
SNP-6200P	refer to SNP- 6200(FW V1.00_12030 2)	H.264 M-JPEG	1	1920x1080	1-way	4/2	Yes	Yes	-	Yes	Supported by design		
SNP- 6200RH	3.02_140722	H.264 M-JPEG	1	1920x1080	1-way	4/2	Yes	Yes	Yes	Yes*			
Note:	Camera is una	ble to ach	ieve ma	ximum FPS wi	th high qua	lity / bitra	ate. (C	amera perf	ormance l	imitation)			



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks
SNP-6320H	1.01_141007	H.264 MJPEG	1	1920x1080	1-way	4/2	Yes	Yes	*2	Yes*	
SNV-1080	Refer to SNO- 1080R(FW 1.00_120125)	H.264 M-JPEG	1	640x480	1-way	1/0	-	Yes	-	Yes	Test by link
SNV-1080R	Refer to SNO- 1080R(FW 1.00_120125	H.264 M-JPEG	1	640×480	1-way	1/0	-	Yes	-	Yes	Test by link
SNV-3080		H.264 MPEG4 M-JPEG	1	720x576	1-way	2/2	-	-	-	-	Supported by design
Note:	Please unchek		time o								
SNV-3082	refer to SND- 3082 (FW	H.264 MPEG4 M-JPEG	1	704x576(PA L) 704x480(NT	1-way	1/1	-	Yes	Yes	Yes	
SNV-3120	v1.24_11081 6	H.264 MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	-	-	Yes	
Note:	PTZ: support		focus.								
SNV-5010	v2.00_11072 7	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	-	-	Yes	-	Yes	
Note:	The frame rat 2.10_111227.	ı	stream (decrease to the	e half if wat	ching dua	al strea	m video. C	amera vei	ndor fix this	issue in FW
SNV-5080	refer to SND- 5080(FW3.10 _130416)		1	1280×1024	1-way	1/1	-	Yes	Yes	Yes	Supported by design
SNV-5080R	3.10_130416	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	-	Yes	Yes	Yes	
Note:	1. SNV-5080 i 2. It's likely fa encountering	ailed to que	ery cam	era parameter		olution co	onfigur	ation. It ha	ppens on S	SNO-5080R	most. When
SNV-5084	1.12_131031 refer to SNB- 5004	H.264 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes	
SNV-6012M	1.00_130704	H264 MJPEG	1	1920×1080	*2	*2	Yes	*2	_	Yes	



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	PTZ	On-Edge Motion	Camera Search Tool	Multi Stream Support	Remarks		
SNV-6084	refere to SND-6083 (FW 1.00_130412)	H264 MJPEG	1	1920×1080	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
SNV-6084R	1.00_130316 refer to SNB- 6004	H264 MJPEG	1	1920×1080	*2	*2	Yes	*2	-	Yes	Supported by design		
SNV-7080	Refer to SND-7080	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	-	Yes	Supported by design		
SNV-7080R	2.00_121004	H.264 MJPEG	1	2048x1536	*2	*2	Yes	Yes	-	Yes*			
SNV-7082	refer to SNB- 7002(1.06_1 30402)	H.264 M-JPEG	1	2048x1536	1-way	1/1	-	Yes	Yes	Yes	Supported by design		
Note:	Sometimes can't get correct UI setting because camera response time too long.												
SNV-7084	Refer to SND- 7084R(0.51	H.264	1	2048x1536	1-way	1/1	-	Yes	-	Yes*	Supported by design		
SNV-7084R	Refer to SND- 7084R(0.51	H.264	1	2048x1536	1-way	1/1	-	Yes	-	Yes*	Supported by design		
SNZ-5200	v1.05_11121 6	H.264 MPEG4 M-JPEG	1	1280x1024	1-way	1/1	Yes	Yes	-	Yes			
SPE-100	v1.19_11031 7	H.264 MPEG4 M-JPEG	1	704x480	1-way	1/1	Yes	Yes	-	Yes			
Note:	SPE-100 PTZ same phenom		-		be stopped	after op	erating	. This is ca	mera FW l	oug, we can	observe the		
SPE-400	S/W: 1.40_120201	H.264 MPEG4 M-JPEG	1	704x480	1-way	4/4	Yes	Yes	-	Yes	Test by link		
Note:	SPE-400 is 4I		els vide	o server	•	B	•	-	•	•			
Note:	All cameras: it's likely failed to query camera parameter in high resolution configuration. It happens on SNO-5080R most. When encountering this issue, please go to camera web.												
Note:	All cameras: i synchronized.	f configurir	ng fixed	frame rate on	camera we	b, param	eter se	election on	NVR web	page won't l	pe		



- : not avaliable on camera

*1: not avaliable on software

*2: not test on software

For multi stream support:

Yes: multi stream fix to A4500kbps/100kbps Yes*: multi stream setting support in Crystal

For PTZ:

Device Name	Tested Firmware	Video Format	Video Ch	Max Resolution	Audio	I/O Ch	1017	IOn-Edge	Search		Remarks
Note:	For Samsung S RTSP. For Samsung S For Samsung S 800*448 & 32	SND-3082 SNB-7002	, SND-3	082/F and SN	B-3002, vid	eo paran	neter: I	brightness	doesn't wo	ork.	J