

**ARM
ELECTRONICS**

ARM YOUR WORLD



Your
Total
Solution
for Video Security



DVR'S ■ MONITORS ■ SPEED DOMES ■ IP CAMERAS
CCTV CAMERAS ■ LENSES ■ UTP HUBS ■ POWER SUPPLIES ■ WIRE

Vol.108A

2008 SYSTEM DESIGN & BUYING GUIDE

ONE SOURCE. TOTAL SOLUTION.

UNLIMITED OPTIONS.

With hundreds of cameras to choose from, ARM is committed to providing customers with quality solutions to fit any application.

MAXIMUM VERSATILITY.

ARM's Wide Dynamic Range, True Day/Night and Super Long Range IR cameras are engineered to overcome challenging environments.

POWERFUL PERFORMANCE.

From high-precision optics, multiple compression formats and superior digital signal processors, ARM products are designed using the most recent advances in video technology.

SECURITY SIMPLIFIED.

System design, set up and operation has never been easier. Let us show you how.

UNPARALLELED SUPPORT.

At ARM Electronics, providing outstanding customer service is a job that does not end with the sale. We are dedicated to being a valued sales and technical resource for you.

**CALL US TODAY AND DISCOVER WHY ARM IS...
YOUR TOTAL SOLUTION FOR VIDEO SECURITY
888.771.4544**

RT8CD SERIES/ RT16CD SERIES



The Real Deal now in
8 & 16 Channels

page 5

VARIFOCAL ASPHERICAL LENSES



Produce Higher Resolution
Images with any Camera

Page 43

WIDE ANGLE BULLET SERIES



Now See 170°
Day or Night
Page 31

TRUE DAY/NIGHT CAMERAS



Capture Superior
Night-Time Images
Page 29

INFRARED MINI DOMES



View Images up to
90' in Total Darkness
Pages 19 & 25

**SUPER HIGH
RESOLUTION LCD'S**



Visualize the
Possibilities
Page 41

**4" SERVICE
MONITOR**



Save Time on
Installation
Page 38

TAKE A LOOK INSIDE

| | | |
|---|------------------------------|-------|
| ■ | Digital Video Recorders | 4-10 |
| | Mobile Recorders | 10 |
| | Real-Time/Time Lapse VCR's | 11 |
| ■ | Speed Domes | 12-14 |
| | Speed Dome Accessories | 15 |
| ■ | Dome Cameras | 16-25 |
| | Professional Cameras | 26-29 |
| | Bullet Cameras | 30-35 |
| | Specialty Cameras | 36-37 |
| ■ | Service & Specialty Monitors | 38-39 |
| | CRT Monitors & Mounts | 40 |
| | LCD Monitors & Mounts | 41 |
| ■ | Multiplexers/Switchers/Quads | 42 |
| | Varifocal Lenses | 43 |
| | Camera Housings & Mounts | 44-45 |
| | Amplifiers & Distributors | 46 |
| | Coax Converters | 47 |
| | UTP Hubs | 47 |
| | Wireless Transmission | 47 |
| | Power Supplies | 48-49 |
| | Bulk Cable & BNC Connectors | 50 |
| | Pre-Made Cables | 51 |

**WIDE ANGLE
VARIFOCAL IR BULLET**



Turn Darkness
Into Detail
Page 33

**SUPER LONG
RANGE IR CAMERAS**



Perfect for Long Distance
Night-Time Detection
Page 35

**SPEED DOME
SERIES**



360° Super Low Lux
Surveillance
Pages 12-14

RT4 Series

4 Channel Real-Time Networkable DVR



PRODUCT FEATURES

- 120 FPS Real-Time Recording
- Up to 750GB Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Looping Camera Inputs
- Video Output (BNC, Master/Call)
- 1 Audio Input /1 Output (RCA)
- Motion Detection
- PTZ Control

RT4CD Series

4 Channel Real-Time Networkable DVR with CD-R/W



PRODUCT FEATURES

- 120 FPS Real-Time Recording
- Up to 750GB Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Looping Camera Inputs
- Video Output (BNC, Master/Call)
- 2 Audio Inputs /1 Output (RCA)
- Motion Detection
- PTZ Control
- USB Offload
- Built in CD-R/W

THE REAL DEAL

Real Time, Real Low Price

| HD SIZE | 4 CHANNEL 120 FPS | 4 CHANNEL/CD-RW 120 FPS |
|---------|-------------------|-------------------------|
| 80GB | RT480G | RT480CD |
| 160GB | RT4160G | RT4160CD |
| 250GB | RT4250G | RT4250CD |
| 320GB | RT4320G | RT4320CD |
| 500GB | RT4500G | RT4500CD |
| 750GB | RT4750G | RT4750CD |

RT8CD/RT16CD Series

Real-Time Networkable DVR with CD-R/W



PRODUCT FEATURES

- Up to 480 FPS Real-Time Recording
- Up to 2.25TB Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Looping Camera Inputs
- Video Output (BNC, Master/Call)
- 4 Audio Inputs / 2 Outputs (RCA)
- Motion Detection
- PTZ Control
- USB Offload
- Built in CD-R/W

| HD SIZE | 8 CHANNEL/CD-RW 240 FPS | 16 CHANNEL/CD-RW 480 FPS |
|---------|-------------------------|--------------------------|
| 160GB | RT8160CD | RT16160CD |
| 250GB | RT8250CD | RT16250CD |
| 320GB | RT8320CD | RT16320CD |
| 500GB | RT8500CD | RT16500CD |
| 640GB | RT8640CD | RT16640CD |
| 1TB | RT81000CD | RT161000CD |
| 1.5TB | RT81500CD | RT161500CD |
| 2.25TB | RT82250CD | RT162250CD |

CAPTURE
VIDEO
AS IT
HAPPENS
In Real Time

DVRCD Series

MPEG-4 Networkable
DVR with CD-R/W

PRODUCT FEATURES

- Up to 480 FPS Real-Time Recording
- Up to 2.25TB Internal Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Looping Camera Inputs
- Video Output
(BNC-Master/Call, VGA, S-Video)
- 1 Audio Input / 1 Output (RCA)
- Motion Detection
- Jog Shuttle for Easy Playback
- PTZ Control
- USB Offload
- Built in CD-R/W



| HD SIZE | 4 CHANNEL 120 FPS | 8 CHANNEL 120 FPS | 8 CHANNEL 240 FPS |
|---------|-------------------|-------------------|-------------------|
| 160GB | DVR4160CD120 | DVR8160CD120 | DVR8160CD240 |
| 250GB | DVR4250CD120 | DVR8250CD120 | DVR8250CD240 |
| 320GB | DVR4320CD120 | DVR8320CD120 | DVR8320CD240 |
| 500GB | DVR4500CD120 | DVR8500CD120 | DVR8500CD240 |
| 640GB | DVR4640CD120 | DVR8640CD120 | DVR8640CD240 |
| 1.0TB | DVR41000CD120 | DVR81000CD120 | DVR81000CD240 |
| 1.5TB | DVR41500CD120 | DVR81500CD120 | DVR81500CD240 |
| 2.25TB | DVR42250CD120 | DVR82250CD120 | DVR82250CD240 |

| HD SIZE | 16 CHANNEL 120 FPS | 16 CHANNEL 480 FPS |
|---------|--------------------|--------------------|
| 160GB | DVR16160CD120 | DVR16160CD480 |
| 250GB | DVR16250CD120 | DVR16250CD480 |
| 320GB | DVR16320CD120 | DVR16320CD480 |
| 500GB | DVR16500CD120 | DVR16500CD480 |
| 640GB | DVR16640CD120 | DVR16640CD480 |
| 1.0TB | DVR161000CD120 | DVR161000CD480 |
| 1.5TB | DVR161500CD120 | DVR161500CD480 |
| 2.25TB | DVR162250CD120 | DVR162250CD480 |

**SECURITY
SIMPLIFIED**
Making it Easy to
Get the Job Done

JDVR Series

JPEG-2000 Networkable
DVR with CD-R/W

PRODUCT FEATURES

- Up to 240 FPS Recording
- Up to 1.5TB Storage
- Triplex Operation
- Networkable
- JPEG-2000 Compression
- Looping Camera Inputs
- Video Output (BNC-Master/Call, VGA)
- 4 Audio Inputs / 1 Output (RCA)
- Motion Detection
- Jog Shuttle for Easy Playback
- PTZ Control
- USB Offload
- Built in CD-R/W



Now Comes
Standard with

AUDIO, VGA OUTPUT & USB OFFLOAD

SUPERIOR IMAGE QUALITY

See the Difference
with Our JDVR Series

DIGITAL VIDEO RECORDERS

| HD SIZE | 4 CHANNEL 120 FPS | 8 CHANNEL 240 FPS | 16 CHANNEL 240 FPS |
|---------|-------------------|-------------------|--------------------|
| 160GB | JDVR4A160CD | JDVR8A160CD | JDVR16A160CD |
| 250GB | JDVR4A250CD | JDVR8A250CD | JDVR16A250CD |
| 320GB | JDVR4A320CD | JDVR8A320CD | JDVR16A320CD |
| 500GB | JDVR4A500CD | JDVR8A500CD | JDVR16A500CD |
| 640GB | JDVR4A640CD | JDVR8A640CD | JDVR16A640CD |
| 1.0TB | JDVR4A1000CD | JDVR8A1000CD | JDVR16A1000CD |
| 1.5TB | JDVR4A1500CD | JDVR8A1500CD | JDVR16A1500CD |



RDVR Series

Real-Time Networkable DVR with Expanded Storage Capability

PRODUCT FEATURES

- Up to 480 FPS Real-Time Recording
- Up to 10.5TB with External Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Looping Camera Inputs
- Video Output (BNC, Master/Call)
- 4 Audio Inputs / 1 Output (RCA)
- Motion Detection
- PTZ Control
- USB Offload

10.5^{TB} Storage With Optional External Hubs

DIGITAL VIDEO RECORDERS

| HD SIZE | 4 CHANNEL 120 FPS | 8 CHANNEL 240 FPS | 16 CHANNEL 480 FPS |
|---------|-------------------|-------------------|--------------------|
| 160GB | RDVR4A160G | RDVR8A160G | RDVR16A160G |
| 250GB | RDVR4A250G | RDVR8A250G | RDVR16A250G |
| 320GB | RDVR4A320G | RDVR8A320G | RDVR16A320G |
| 500GB | RDVR4A500G | RDVR8A500G | RDVR16A500G |
| 640GB | RDVR4A640G | RDVR8A640G | RDVR16A640G |
| 1.0TB | RDVR4A1000G | RDVR8A1000G | RDVR16A1000G |
| 1.5TB | RDVR4A1500G | RDVR8A1500G | RDVR16A1500G |

JBOD Series

Expand Your Storage



| HD SIZE | JBOD | JBOD HUB |
|---------|---------------|-----------------|
| 500GB | RDVRJBOD500G | RDVRJBOD500HUB |
| 1.0TB | RDVRJBOD1000G | RDVRJBOD1000HUB |
| 1.5TB | RDVRJBOD1500G | RDVRJBOD1500HUB |
| 2.25TB | RDVRJBOD2250G | RDVRJBOD2250HUB |

These Expanded Storage Devices Offer the Capability of Linking One JBODHUB to Three JBODS for a Total of 9.0TB's

For use with the RDVR Series only.

PCDVR Series

16 and 32 Channel PC-Based DVR'S



ADVANCED DIGITAL RECORDING

PRODUCT FEATURES

- Up to 240 FPS Recording
- Up to 3TB Internal Storage
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Video Input (BNC)
- Video Output (SVGA, BNC-Call)
- 2 Audio Inputs (RCA)
- Built in DVD-R/W
- PTZ Control
- Motion Detection
- E-mail Notification
- 4U Rack Mountable

NOW COMES
STANDARD WITH
DVD-R/W

| HD SIZE | 16 CHANNEL 120 FPS | 32 CHANNEL 240 FPS | 16 CHANNEL 480 FPS | 32 CHANNEL 480 FPS |
|---------|--------------------|--------------------|--------------------|--------------------|
| 500GB | PCDVR16A500G120 | PCDVR32A500G240 | DRX16A500P480 | DRX32A500P480 |
| 1TB | PCDVR16A1000G120 | PCDVR32A1000G240 | DRX16A1000P480 | DRX32A1000P480 |
| 1.5TB | PCDVR16A1500G120 | PCDVR32A1500G240 | DRX16A1500P480 | DRX32A1500P480 |
| 2.0TB | PCDVR16A2000G120 | PCDVR32A2000G240 | DRX16A2000P480 | DRX32A2000P480 |
| 2.5TB | PCDVR16A2500G120 | PCDVR32A2500G240 | DRX16A2500P480 | DRX32A2500P480 |
| 3.0TB | PCDVR16A3000G120 | PCDVR32A3000G240 | DRX16A3000P480 | DRX32A3000P480 |

DRX Series

16 and 32 Channel PC-Based DVR's with Cash Register Interface



NOW COMES
STANDARD WITH
DVD-R/W

POINT OF SALE INTERFACE

PRODUCT FEATURES

- 480 FPS Recording
- Up to 3TB Internal Storage
- Cash Register Interface
- Triplex Operation
- Networkable
- MPEG-4 Compression
- Video Input (BNC)
- Video Output (SVGA, BNC-Call)
- Audio Inputs (RCA 16 Channels)
- Built in DVD-R/W
- PTZ Control
- Motion Detection
- E-mail Notification
- 4U Rack Mountable



4 Channel DVR with USB PC Link

PRODUCT FEATURES

- 30 FPS Recording
- Up to 750GB Internal Storage
- M-JPEG Compression
- Looping Camera Inputs
- Video Output BNC (Master/Call)
- Motion Detection

| HD SIZE | EZDVR SERIES |
|---------|--------------|
| 160GB | EZDVR4160G |
| 250GB | EZDVR4250G |
| 320GB | EZDVR4320G |
| 500GB | EZDVR4500G |
| 750GB | EZDVR4750G |

4 Channel Mobile DVR with Audio and GPS MDVR4A80GPS



PRODUCT FEATURES

- 30 FPS Recording
- Up to 250GB Storage
- M-JPEG Compression
- GPS Position, Signal and Speed Overlay
- Motion Detection
- 12VDC Operation

| HD SIZE | MDVR4GPS SERIES |
|---------|-----------------|
| 80GB | MDVR4A80GPS |
| 160GB | MDVR4A160GPS |
| 250GB | MDVR4A250GPS |

Mobile 960 Hour Time Lapse VCR MVCR960



PRODUCT FEATURES

- Up to 30 HR Real-Time Recording with T-120
- Up to 960 HR Time Lapse Recording with T-160
- 1 Channel Audio Recording
- 4 Head Double Azimuth Scan
- 12VDC Operation

GO MOBILE

8 Hour Real-Time, Half Size Chassis Casino Recorder VCR800



PRODUCT FEATURES

- Half Size Design for Side by Side Mounting
- Three Recording Modes 8-24-40 HR with T-160
- 100 Second High Speed Rewind
- Time/Date Search, Alarm Search, Alarm Scan
- Master/Slave Clock Adjustment
- Tape Protection Functions
- 4 Head Azimuth Helical Scan

Jog Shuttle for Quick Search & Slow-Motion Playback



30 Hour Real- Time/960 Hour Time Lapse VCR with Jog Shuttle VCR30RT960J

PRODUCT FEATURES

- Up to 30 HR Real-Time Recording with T-120
- Up to 960 HR Time Lapse Recording with T-120
- Time/Date Display
- Includes Wireless Remote
- 1 Channel Audio Recording
- Repeat, Timer, Alarm & Series Recording Modes
- 4 Head Double Azimuth Scan

REAL-TIME/TIME LAPSE VCR'S



18x
25x

indoor

Shown with optional flush mount kit SDFMT

SPEED DOMES

Exview Day/Night Indoor Speed Domes

ICD18XSD

18X Optical Zoom

ICD25XSD

25X Optical Zoom

exview

PRODUCT FEATURES

- 480 Lines of Resolution
- Day/Night Operation
- 1/4" Exview Imaging Device
- Up to 25X Zoom (ICD25XSD)
- Pan Speed 0-300°/Second
- Tilt Speed 0-60°/Second
- 24VAC Power (15VA)
- Multi-Protocol RS-485
- Alarm Function
- 128 Presets
- Tour Function (6 Max)
- Operating Temp (14°F-122°F)
- Weight (4.41 lbs)

RECOMMENDED ACCESSORIES

- | | |
|---------------|---|
| SDKBD1 | Basic Keyboard Controller |
| SDKBD2 | Full Functional Keyboard Controller |
| SDKBD3 | Full Functional Keyboard with 3-Axis Joystick |
| SDFMT | Indoor Flush Mount Kit |

day
night



SDKBD1



SDKBD2 SDKBD3



SDFMT

Exview Day/Night Outdoor Speed Domes

OCD18XSD
18X Optical Zoom

OCD25XSD
25X Optical Zoom

day
night

RECOMMENDED ACCESSORIES

- SDKBD1** Basic Keyboard Controller
- SDKBD2** Full Functional Keyboard Controller
- SDKBD3** Full Functional Keyboard with 3-Axis Joystick
- WX10024UL** Weatherproof 100VA Power Supply

exview

PRODUCT FEATURES

- 480 Lines of Resolution
- Day/Night Operation
- 1/4" Exview Imaging Device
- Up to 25X Optical Zoom (OCD25XSD)
- Pan Speed 0-300°/Second
- Tilt Speed 0-60°/Second
- 24VAC Power (30VA)
- Multi-Protocol RS-485
- Alarm Function
- 128 Presets
- Tour Function (6 Max)
- Operating Temp (14°F-122°F)
- Weight (8.82 Lbs)

outdoor



SPEED DOMES

outdoor

18X Exview Speed Domes

OC18XSD

Outdoor

IC18XSD

Indoor



*Shown with optional
flush mount kit SDFMT*

PRODUCT FEATURES

- 480 Lines of Resolution
- 1/4" Exview Imaging Device
- 18X Optical Zoom
- Pan Speed 0-300°/Second
- Tilt Speed 0-60°/Second
- 24VAC Power (15VA Indoor 30VA Outdoor)
- Multi-Protocol RS-485
- Alarm Function
- 128 Presets
- Tour Function (6 Max)
- Operating Temp (14°F-122°F)
- Weight (4.41 / 8.82 lbs., Indoor/Outdoor)

RECOMMENDED ACCESSORIES

- SDKBD1** Basic Keyboard Controller
- SDKBD2** Full Functional Keyboard Controller
- SDKBD3** Full Functional Keyboard W/ 3-Axis Joystick
- WX10024UL** Weatherproof 100VA Power Supply



SDKBD1



SDKBD2 SDKBD3

indoor

Speed Dome Accessories

Mounts, Controllers, Adapters



SDKBD2 SDKBD3

- SD6FTEX 6' Extension Kit
- SDADAPTER Metric Pipe to 1-1/2" NPT Adapter *(Not Pictured)*
- SDFMT Indoor Flush Mount Kit
- SDICA Inside Corner Adapter
- SDKBD1 Basic Keyboard Controller
- SDKBD2 Full Function Keyboard Controller
- SDKBD3 Full Function Keyboard with 3-Axis Joystick
- SDOCA Outside Corner Adapter
- SDPA Pole Adapter
- SDPED Pedestal Adapter
- SDRA Right Angle Adapter
- WX10024UL 100VA Weatherproof Power Supply



SDKBD1

Adapters & mounts



SD6FTEX



SDRA



SDICA



SDFMT



SDOCA



SDPED



WX10024UL



SDPA

colormini



Color Mini Dome Cameras

C420MD

White Camera Case

C420MDBLK

Black Camera Case

PRODUCT FEATURES

- 420 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (150mA)
- Lux (0.8 @ F2.0)
- BNC Video Output
- Dimensions (3.9" x 3.5")
- Weight (0.36 lbs)
- Operating Temp (14°F-113°F)
- Indoor

Color Mini Dome Camera

C480MD

White Camera Case

PRODUCT FEATURES

- 480 Lines of Resolution
- 1/4" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (100mA)
- Lux (0.1 @ F2.0)
- BNC Video Output
- Dimensions (2.9" x 2.2")
- Weight (0.31 lbs)
- Operating Temp (14°F-122°F)
- Indoor

Color Varifocal Mini Dome Cameras

C380MDVMI

4-9mm Manual Iris Lens

C480MDVMI

4-9mm Manual Iris Lens

C480MD2VMI

2.6-6mm Manual Iris Lens

Color Varifocal Mini Dome Day/Night Cameras

C380MDVMIDN

4-9mm Manual Iris Lens

C480MDVMIDN

4-9mm Manual Iris Lens

C480MD2VMIDN

2.6-6mm Manual Iris Lens

Color Varifocal Mini Dome Cameras

C420MDVAIDC

Varifocal Auto Iris Lens

C481MDVAIDC

Varifocal Auto Iris Lens



PRODUCT FEATURES

- 380 or 480 Lines of Resolution
- Day/Night Operation (DN Models)
- 1/3" Imaging Device
- Varifocal Manual Iris Lens
- 3-Axis Camera Mount
- 12VDC Power (350mA)
- Lux (1.0 @ F1.2)
- Lux (1.0 @ F1.2) / Night (0.01) (DN Models)
- BNC Video Output
- Dimensions (4.5" x 3.4")
- Weight (0.5 Lb)
- Operating Temp (14°F-113°F)
- Indoor

PRODUCT FEATURES

- 420 or 480 Lines of Resolution
- 1/3" Imaging Device
- 4-9mm Auto Iris Lens
- 12VDC Power (120mA)
- Lux (0.5 @ F1.6)
- BNC Video Output
- Dimensions (4.8"x 3.3"x 5.2")
- Weight (0.6 lbs)
- Operating Temp (32°F-122°F)
- Indoor





Indoor Mini Dome Wall Mount
MDWMT



Color Varifocal Mini Dome Cameras

HIGH RESOLUTION

C540MDVAI

4-9mm Auto Iris Lens

C540MD2VAI

2.6-6mm Auto Iris Lens

SUPER HIGH RESOLUTION

C620MDVAI

4-9mm Auto Iris Lens

C620MD2VAI

2.6-6mm Auto Iris Lens



B/W Super High Resolution Mini Dome Cameras

B600MDVAI

4-9mm Auto Iris Lens

B600MD2VAI

2.6-6mm Auto Iris Lens

PRODUCT FEATURES

- 600 Lines of Resolution
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.01 @ F1.2)
- BNC Video Output
- Dimensions (4.7" x 3.9")
- Weight (1.1 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (MDWMT)
- Indoor

EXVIEW HIGH RESOLUTION

CX580MDVAI

4-9mm Auto Iris Lens

CX580MD2VAI

2.6-6mm Auto Iris Lens

PRODUCT FEATURES

- 540-620 Lines of Resolution
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.7 @ F1.2) (540)
- Lux (0.5 @ F1.2) (620)
- Lux (0.1 @ F1.2) (580)
- BNC Video Output
- Dimensions (4.7" x 3.9")
- Weight (1.1 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (MDWMT)
- Indoor

Color Varifocal Day / Night Mini Dome Cameras

HIGH RESOLUTION

C540MDVAIDN

4-9mm Auto Iris Lens

C540MD2VAIDN

2.6-6mm Auto Iris Lens

SUPER HIGH RESOLUTION

C620MDVAIDN

4-9mm Auto Iris Lens

C620MD2VAIDN

2.6-6mm Auto Iris Lens

EXVIEW HIGH RESOLUTION

CX580MDVAIDN

4-9mm Auto Iris Lens

CX580MD2VAIDN

2.6-6mm Auto Iris Lens

PRODUCT FEATURES

- 540-620 Lines of Resolution
- Day/Night Operation
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.7 @ F1.2) / Night (0.01) (540)
- Lux (0.5 @ F1.2) / Night (0.01) (620)
- Lux (0.1 @ F1.2) / Night (0.003) (580)
- BNC Video Output
- Dimensions (4.7" x 3.9")
- Weight (1.1 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (MDWMT)
- Indoor



DAYNIGHT

Color Varifocal Infrared Mini Dome Cameras

C540MDVAIDNIR

540 Lines of Resolution

C620MDVAIDNIR

620 Lines of Resolution

CX580MDVAIDNIR

Exview 580 Lines of Resolution

PRODUCT FEATURES

- 540-620 Lines of Resolution
- Day/Night Operation
- 1/3" Imaging Device
- 3.7-12mm Aspherical IR Lens
- True Day Night Cut Filter
- Up to 90' Illumination
- 3-Axis Camera Mount
- Dual Voltage Power (750mA)
- Lux (0.0 Built in IR on)
- BNC Video Output
- Dimensions (4.7" x 3.9")
- Weight (1.4 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (MDWMT)
- Indoor





B/W Super High Resolution Varifocal Vandal Dome Cameras

B600MDVAIVP

4-9mm Auto Iris Lens

B600MD2VAIVP

2.6-6mm Auto Iris Lens

PRODUCT FEATURES

- 600 Lines of Resolution
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.01 @ F1.2)
- BNC Video Output
- Dimensions (6.4" x 3.9")
- Weight (1.98 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)

Vandal Dome
Wall Mount
VPMDWMT



vandal PROOF

Color Vandal Dome Cameras

C380MDVP

380 Lines of Resolution

C480MDVP

480 Lines of Resolution

PRODUCT FEATURES

- 380 or 480 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (110mA)
- Lux (0.5 @ F1.2)
- BNC Video Output
- Dimensions (3.75" x 2.76")
- Weight (0.84 lbs)
- Operating Temp (14°F-122°F)
- Weatherproof



Color 5-50mm Vandal Dome Cameras

HIGH RESOLUTION

C540MD5VAIVP

540 Lines of Resolution

C540MD5VAIVPDN

Day/Night 540 Lines of Resolution

SUPER HIGH RESOLUTION

C620MD5VAIVP

620 Lines of Resolution

C620MD5VAIVPDN

Day/Night 620 Lines of Resolution

EXVIEW HIGH RESOLUTION

CX580MD5VAIVP

580 Lines of Resolution

CX580MD5VAIVPDN

Day/Night 580 Lines of Resolution

5-50 mm
LENS

PRODUCT FEATURES

- 540-620 Lines of Resolution
- Day/Night Operation (DN Models)
- 1/3" Imaging Device
- 5-50mm Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.7 @ F1.2) / Night (0.01) (540)
- Lux (0.5 @ F1.2) / Night (0.01) (620)
- Lux (0.1 @ F1.2) / Night (0.003) (580)
- BNC Video Output
- Dimensions (6.4" x 5.5")
- Weight (2.65 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)

**LONG
RANGE,
LOW LIGHT
PRECISION**
WITH ARM RELIABILITY

Color Varifocal Vandal Dome Cameras

HIGH RESOLUTION

C540MDVAIVP

4-9mm Auto Iris Lens

C540MD2VAIVP

2.6-6mm Auto Iris Lens

C540MD9VAIVP

9-22mm Auto Iris Lens

SUPER HIGH RESOLUTION

C620MDVAIVP

4-9mm Auto Iris Lens

C620MD2VAIVP

2.6-6mm Auto Iris Lens

C620MD9VAIVP

9-22mm Auto Iris Lens

EXVIEW HIGH RESOLUTION

CX580MDVAIVP

4-9mm Auto Iris Lens

CX580MD2VAIVP

2.6-6mm Auto Iris Lens

CX580MD9VAIVP

9-22mm Auto Iris Lens



VANDALPROOF

PRODUCT FEATURES

- 540-620 Lines of Resolution
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.7 @ F1.2) (540)
- Lux (0.5 @ F1.2) (620)
- Lux (0.1 @ F1.2) (580)
- BNC Video Output
- Dimensions (6.4" x 3.9")
- Weight (1.98 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMTG)
- Weatherproof (IP66)



Gooseneck
Vandal Dome
Wall Mount
VPMDWMTG



Color Varifocal Day/Night Vandal Dome Cameras

HIGH RESOLUTION

C540MDVAIVPDN

4-9mm Auto Iris Lens

C540MD2VAIVPDN

2.6-6mm Auto Iris Lens

C540MD9VAIVPDN

9-22mm Auto Iris Lens

SUPER HIGH RESOLUTION

C620MDVAIVPDN

4-9mm Auto Iris Lens

C620MD2VAIVPDN

2.6-6mm Auto Iris Lens

C620MD9VAIVPDN

9-22mm Auto Iris Lens

EXVIEW HIGH RESOLUTION

CX580MDVAIVPDN

4-9mm Auto Iris Lens

CX580MD2VAIVPDN

2.6-6mm Auto Iris Lens

CX580MD9VAIVPDN

9-22mm Auto Iris Lens

DAYNIGHT

PRODUCT FEATURES

- 540-620 Lines of Resolution
- Day/Night Operation
- 1/3" Imaging Device
- Varifocal Auto Iris Lens
- 3-Axis Camera Mount
- Dual Voltage Power (350mA)
- Lux (0.7 @ F1.2) / Night (0.01) (540)
- Lux (0.5 @ F1.2) / Night (0.01) (620)
- Lux (0.1 @ F1.2) / Night (0.003) (580)
- BNC Video Output
- Dimensions (6.4" x 3.9")
- Weight (1.98 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)



Vandal Dome
Wall Mount
VPMDWMT

exview

Color Infrared Vandal Dome Cameras

C420MDVPIR

420 Lines of Resolution

C480MDVPIR

480 Lines of Resolution

Color Varifocal Infrared Vandal Dome Cameras

C420MDVMIVPIR

420 Lines of Resolution

C480MDVMIVPIR

480 Lines of Resolution

FIXED FOCAL



PRODUCT FEATURES

- 420 or 480 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- Up to 45' Illumination
- 12VDC Power (500mA)
- Lux (0.0 Built in IR on)
- BNC Video Output
- Dimensions (3.7"x 3.14")
- Weight (0.53 lbs)
- Operating Temp (14°F-122°F)
- Weatherproof



VARIFOCAL

PRODUCT FEATURES

- 420 or 480 Lines of Resolution
- 1/3" Imaging Device
- 4-9mm Varifocal Lens
- Up to 45' Illumination
- 12VDC Power (500mA)
- Lux (0.0 Built in IR on)
- BNC Video Output
- Dimensions (4.75"x 3.8")
- Weight (0.89 lbs)
- Operating Temp (14°F-122°F)
- Weatherproof



Color Varifocal Infrared Vandal Dome Cameras

C540MDVAIVPDNIR

540 Lines of Resolution

C620MDVAIVPDNIR

620 Lines of Resolution

CX580MDVAIVPDNIR

Exview 580 Lines of Resolution

PRODUCT FEATURES

- 540-620 Lines of Resolution
- Day/Night Operation
- 1/3" Imaging Device
- 3.7-12mm Aspherical IR Lens
- True Day Night Cut Filter
- Up to 90' Illumination
- 3-Axis Camera Mount
- Dual Voltage Power (750mA)
- Lux (0.0 Built in IR on)
- BNC Video Output
- Dimensions (6.4" x 3.9")
- Weight (1.98 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)

NEW DESIGN

PREVENTS IR BOUNCE BACK
AND OVER-EXPOSURE

UPGRADED IR LENS

ASPHERICAL IR-SENSITIVE LENS
ELIMINATES FOCUS SHIFT

ADDITIONAL LED'S

FOR EXTENDED IR RANGE
UP TO 90 FEET

RECOMMENDED POWER SUPPLIES

12VDC15AMP or AC2440VA

(See Page 48)

B/W Professional Cameras

B480

Standard Resolution

BX600

Super High Resolution



PRODUCT FEATURES

- 480 or 600 Lines of Resolution
 - 1/3" Imaging Device (B480)
 - 1/3" Exview Imaging Device (BX600)
 - C/CS Type Lens, Video or DC Drive
 - Dual Voltage Power (300mA)
 - Lux (0.02 @ F1.4)
 - Lux (0.002 @ F1.4) (BX600)
 - BNC Video Output
 - Dimensions (2.4"x 2.6"x 5")
 - Weight (1.76 lbs)
 - Operating Temp (14°F-140°F)
- Lens sold separately
(See Page 43)*

THE PICTURE QUALITY YOU NEED AT THE PRICE YOU WANT

Color Professional Cameras

C420

Standard Resolution

C420A

Standard Resolution with Audio

C550

High Resolution

C550A

High Resolution with Audio



PRODUCT FEATURES

- 420 or 550 Lines of Resolution
 - 1/3" Imaging Device
 - C/CS Type Lens, Video or DC Drive
 - Dual Voltage Power (300mA)
 - Lux (0.5 @ F1.4)
 - BNC Video Output
 - Dimensions (2.4"x 2.6"x 5")
 - Weight (1.76 lbs)
 - Operating Temp (14°F-140°F)
- Lens sold separately
(See Page 43)*

REACH A HIGHER STANDARD

Color Professional Cameras

C600

Super High Resolution

CX550

Exview High Resolution



PRODUCT FEATURES

- 550 or 600 Lines of Resolution
- 1/3" Imaging Device
- 1/3" Exview Imaging Device (CX550)
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.5 @ F1.4)
- Lux (0.03 @ F1.4) (CX550)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*

CAPTURE CLEAR IMAGES UNDER EXTREME LIGHTING CONDITIONS

Wide Dynamic Professional Camera

C550WD



PRODUCT FEATURES

- 550 Lines of Resolution
- 1/3" Imaging Device
- Wide Dynamic DSP
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.5 @ F1.4)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*

ELIMINATE GLARE

built-in IR CUT FILTER



Color Day/Night Professional Camera C420DN

PRODUCT FEATURES

- 420 Lines of Resolution
- 1/3" Imaging Device
- True Day/Night IR Cut Filter
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.5 @ F1.4) / Night (0.01)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*

Color High Resolution Day/Night Professional Camera C550DN

PRODUCT FEATURES

- 550 Lines of Resolution
- 1/3" Imaging Device
- True Day/Night IR Cut Filter
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.5 @ F1.4) / Night (0.01)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*



Color Super High Resolution Day/Night Professional Camera C600DN

PRODUCT FEATURES

- 600 Lines of Resolution
- 1/3" Imaging Device
- True Day/Night IR Cut Filter
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.5 @ F1.4) / Night (0.01) (C600DN)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*



Color High Resolution Exview Day/Night Professional Camera CX550DN

PRODUCT FEATURES

- 550 Lines of Resolution
- 1/3" Exview Imaging Device
- True Day/Night IR Cut Filter
- C/CS Type Lens, Video or DC Drive
- Dual Voltage Power (300mA)
- Lux (0.03 @ F1.4) / Night (0.003)
- BNC Video Output
- Dimensions (2.4"x 2.6"x 5")
- Weight (1.76 lbs)
- Operating Temp (14°F-140°F)

*Lens sold separately
(See Page 43)*

true day/night



B/W Bullet Camera B380BC

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (100mA)
- Lux (0.1 @ F2.0)
- BNC Video Output
- Dimensions (0.9"x 3")
- Weight (0.22 lbs)
- Operating Temp (14°F-122°F)
- Weatherproof

B/W Exview Bullet Camera BX600BC

PRODUCT FEATURES

- 600 Lines of Resolution
- 1/3" Exview Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (100mA)
- Lux (0.003 @ F1.2)
- BNC Video Output
- Dimensions (0.7"x 2.36")
- Weight (0.23 lbs)
- Operating Temp (24°F-104°F)
- Weatherproof



POINT AIM CAPTURE



Color Bullet Camera C380BC

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/4" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (160mA)
- Lux (0.1 @ F2.0)
- Dimensions (0.8"x 2.3")
- Weight (0.22 lbs)
- Operating Temp (14°F-122°F)
- Weatherproof



Color Day/Night Bullet Camera C420BCDN

PRODUCT FEATURES

- 420 Lines of Resolution
- Day/Night Operation
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (150mA)
- Lux (0.01 @ F1.2)
- Dimensions (1.4"x 4.9")
- Weight (0.46 lbs)
- Operating Temp (12°F-122°F)
- Weatherproof



Color Bullet Camera C480BC

PRODUCT FEATURES

- 480 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (120mA)
- Lux (0.4 @ F2.0)
- Dimensions (1.8"x 2.6")
- Weight (1.0 lbs)
- Operating Temp (14°-131°F)
- Weatherproof

170°

WIDE ANGLE

FIELD OF VIEW



Color Wide Angle Bullet Cameras

C420BCWA

Standard Resolution

C420BCDNWA

Standard Resolution Day/Night

C520BCWA

High Resolution

C520BCDNWA

High Resolution Day/Night

CX520BCWA

Exview High Resolution

CX520BCDNWA

Exview High Resolution Day/Night

PRODUCT FEATURES

- 420-520 Lines of Resolution
- Day/Night Operation (DN Models)
- 1/3" Imaging Device (C420, C520)
- 1/3" Exview Imaging Device (CX520)
- 2.2mm Wide Angle Mini Lens
- 12VDC Power (115mA)
- Lux (0.5 @ F2.0) (C420, C520)
- Lux (0.05 @ F2.0) (CX520)
- Dimensions (1.5"x 2.5")
- Weight (0.4 lbs)
- Operating Temp (14°-122°F)
- Weatherproof

Color Varifocal Bullet Cameras

C420BCVF

Standard Resolution

C420BCDNVF

Standard Resolution Day/Night

C520BCVF

High Resolution

C520BCDNVF

High Resolution Day/Night

CX520BCVF

Exview High Resolution

CX520BCDNVF

Exview High Resolution Day/Night

PRODUCT FEATURES

- 420-520 Lines of Resolution
- Day/Night Operation (DN Models)
- 1/3" Imaging Device (C420, C520)
- 1/3" Exview Imaging Device (CX520)
- 4-9mm Varifocal Lens
- External Lens Adjustment
- 12VDC Power (350mA)
- Lux (0.5 @ F2.0) (C420, C520)
- Lux (0.05 @ F2.0) (CX520)
- Dimensions (1.4"x 4.9")
- Weight (0.8 lbs)
- Operating Temp (14°-122°F)
- Weatherproof



Color IR Bullet Camera C380BCIR

PRODUCT FEATURES

- 380 Lines of Resolution
- 30' IR Range
- 1/3" Imaging Device
- 4mm Mini Lens
- 12VDC Power (260mA)
- Lux (0.0 Built in IR on)
- Dimensions (2.5"x 4.1")
- Weight (1.3 lbs)
- Operating Temp (14°-122°F)
- Weatherproof



Color IR Bullet Cameras

C420BCIR60

60' Range

C420BCIR120

120' Range

PRODUCT FEATURES

- 420 Lines of Resolution
- 60' or 120' IR Range
- 1/3" Imaging Device
- 6mm Mini Lens
- 12VDC Power (750mA)
- Lux (0.0 Built in IR on)
- Dimensions (2.4"x 4.3") 60'
- Dimensions (3.9"x 7.1") 120'
- Weight (0.8 lbs) 60'
- Weight (1.0 lbs) 120'
- Operating Temp (24°-104°F)
- Weatherproof



C420BCIR120



C420BCIR60

SEE IN TOTAL DARKNESS



Color 150' IR Heavy Duty Camera

C480HDCIR150

PRODUCT FEATURES

- 480 Lines of Resolution
- 150' IR Range
- 1/3" Imaging Device
- 8mm Mini Lens
- 12VDC Power (1AMP)
- Lux (0.0 Built in IR on)
- Dimensions (5.7"x 4.5"x 13.6")
- Weight (3.8 lbs)
- Operating Temp (24°-104°F)
- Weatherproof

* Recommended Mount OCHWMT



2.8-11mm

WIDE ANGLE ASPHERICAL IR LENS

Color Varifocal
IR Bullet Camera
C420BCDNVFIR

Color High Resolution
Varifocal
IR Bullet Camera
C520BCDNVFIR

PRODUCT FEATURES

- 420 or 520 Lines of Resolution
- Day/Night Operation
- 49' IR Range
- 1/4" Imaging Device
- 2.8-11mm Aspherical IR Lens
- External Lens Adjustment
- 12VDC Power (390mA)
- Lux (0.0 Built in IR on)
- Dimensions (3.5"x 4.1")
- Weight (1.2 lbs)
- Operating Temp (14°-113°F)
- Weatherproof

Color Varifocal IR Bullet Camera C420BCVFIR

PRODUCT FEATURES

- 420 Lines of Resolution
- Day/Night Operation
- 80' IR Range
- 1/3" Imaging Device
- 4-9mm Auto Iris Lens
- External Lens Adjustment
- 12VDC Power (500mA)
- Lux (0.0 Built in IR on)
- Dimensions (3.1"x 3.2"x 6.2")
- Weight (1.3 lbs)
- Operating Temp (14°-122°F)
- Weatherproof



VARIFOCAL

Color Varifocal IR Vandal Proof Bullet Camera C420BCVAIVPIR

PRODUCT FEATURES

- 420 Lines of Resolution
- Day/Night Operation
- 100' IR Range
- Pass Through Cable Mount
- 1/3" Imaging Device
- 4-9mm Auto Iris Lens
- External Lens Adjustment
- Dual Voltage Power (632mA)
- Lux (0.0 Built in IR on)
- Dimensions (3.1"x 7.8")
- Weight (7.7 lbs)
- Operating Temp (24°-104°F)
- Weatherproof



Color High Resolution Varifocal IR Heavy Duty Cameras

C520HDCVFIR280DC

12VDC, 280' IR Range

C520HDCVFIR280AC

24VAC, 280' IR Range

RECOMMENDED POWER SUPPLIES

12VDC15AMP (DC Model)

WX10024UL (AC Model)

280'
IR Range

GO THE DISTANCE

WITH THESE SUPER LONG RANGE
HIGH RESOLUTION CAMERAS

PRODUCT FEATURES

- 520 Lines of Resolution
- 280' or 492' IR Range
- 1/3" Imaging Device
- 5-50mm Auto Iris Lens
- 12VDC or 24VAC Models (1.2AMP)
- Lux (0.0 Built in IR on)
- Dimensions (5"x 6.14"x 13.9")
- Weight (7.7 lbs)
- Operating Temp (14°-122°F)
- Mount Included
- Weatherproof

BULLET CAMERAS

Color High Resolution Varifocal IR Heavy Duty Cameras

C520HDCVFIR492DC

12VDC, 492' IR Range

C520HDCVFIR492AC

24VAC, 492' IR Range

492'
IR Range

RECOMMENDED POWER SUPPLIES

12VDC15AMP (DC Model)

WX10024UL (AC Model)



Color Side View Smoke Detector Camera C380SDCS

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/4" Imaging Device
- 3.6mm Pinhole Mini Lens
- 12VDC Power (100mA)
- Lux (0.3 @ F2.0)
- Dimensions (4.9"x 2.1")
- Weight (0.45 lbs)
- Operating Temp (14°-122°F)
- Indoor

Color PIR Camera C380PIR

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/3" Imaging Device
- 3.7mm Pinhole Mini Lens
- 12VDC Power (100mA)
- Lux (0.1 @ F3.5)
- Dimensions (3.1"x 4.5"x 5.7")
- Weight (0.2 lbs)
- Operating Temp (14°-122°F)
- Mount Included
- Indoor



GET BIG RESULTS WITH THESE MINI CAMERAS



B/W Metal-Cased Camera B380MC

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (110mA)
- Lux (0.1 @ F2.8)
- Dimensions (1.3"x 1.3"x 0.5")
- Weight (0.04 lbs)
- Operating Temp (14°-113°F)
- Indoor



Color Metal-Cased Camera C380MC

PRODUCT FEATURES

- 380 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (140mA)
- Lux 2.0 @ F2.0
- Dimensions (1.5"x 1.4"x 0.7")
- Weight (0.13 lbs)
- Operating Temp (14°-113°F)
- Indoor



Color High Resolution Metal-Cased Camera C480MC

PRODUCT FEATURES

- 480 Lines of Resolution
- 1/3" Imaging Device
- 3.6mm Mini Lens
- 12VDC Power (100mA)
- Lux 1.0 @ F1.2
- Dimensions (1.5"x 1.4"x 0.7")
- Weight (0.13 lbs)
- Operating Temp (14°-113°F)
- Indoor



Dummy Professional Camera with Lens DPROCAM



Vandal 6.5" Dummy Domes DMDVPW (White Case) DMDVPB (Black Case) DMDVP (Grey Case)



Indoor 6" Dummy Domes DMD6W (White Case) DMD6 (Black Case)



BE ANYWHERE

WITH THESE IP VANDAL
DOME CAMERAS

Color Varifocal Vandal IP Dome Cameras

HIGH RESOLUTION

IP540MDVAIVP

4-9mm Auto Iris Lens

IP540MD5VAIVP

5-50mm Auto Iris Lens

SUPER HIGH RESOLUTION

IP620MDVAIVP

4-9mm Auto Iris Lens

IP620MD5VAIVP

5-50mm Auto Iris Lens

PRODUCT FEATURES

- 540 or 620 Lines of Resolution
- 1/3" Imaging Device
- 4-9mm or 5-50mm Auto Iris Lens
- 12VDC Power (750mA)
- 3-Axis Camera Mount
- Web Interface (Browser Based)
- Compression (MPEG 4)
- 30FPS Real-Time Recording
- Lux (0.7 @ F1.2) (IP540)
- Lux (0.5 @ F1.2) (IP620)
- BNC Video Output
- Dimensions (6.4"x 3.9") (4-9mm)
- Dimensions (6.4"x 5.5") (5-50mm)
- Weight (1.98 lbs) (4-9mm)
- Weight (2.65 lbs) (5-50mm)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)



Color Varifocal Vandal Infrared IP Dome Cameras

HIGH RESOLUTION

IP540MDVAIVPDNIR

3.7-12mm Auto Iris Lens

SUPER HIGH RESOLUTION

IP620MDVAIVPDNIR

3.7-12mm Auto Iris Lens

PRODUCT FEATURES

- 540 or 620 Lines of Resolution
- 1/3" Imaging Device
- 3.7-12mm Aspherical IR Lens
- True Day Night Cut Filter
- Up to 90' Illumination
- 12VDC Power (750mA)
- 3-Axis Camera Mount
- Web Interface (Browser Based)
- Compression (MPEG-4)
- 30FPS Real-Time Recording
- Lux (0.0 Built in IR on)
- BNC Video Output
- Dimensions (6.4"x 3.9")
- Weight (1.98 lbs)
- Operating Temp (14°F-122°F)
- Optional Wall Mount (VPMDWMT)
- Weatherproof (IP66)

Portability



3.5" LCD Service Monitor 35SMKIT

PRODUCT FEATURES

- 3.5" TFT Display
- Built in 3.5W Speaker
- Operates on 8 "AA" Batteries
- BNC Video Input
- Resolution (480x234)
- Brightness (200cd/m2)
- Dimensions (3.1" x 1.1" x 4.4")
- Weight (0.5 lbs)

INCLUDES:

Protective Carry Case with Belt Clip & Neck Strap

4" LCD Service Monitor 4SMKIT

PRODUCT FEATURES

- 4" TFT Display
- External Volume Control
- External Brightness/Color Control
- Looping BNC Video Input
- Looping RCA Audio Input
- Resolution (480x234)
- Brightness (350nit)
- Dimensions (4.1"x 6"x 1.5")
- Weight (0.7 lbs)

INCLUDES:

Protective Carry Case with Arm Strap & Neck Strap,
6 "AA" Batteries and 12VDC Charger.

Durability



SAVE TIME WITH THESE HAND-HELD SERVICE MONITORS

Mobility



5.6" LCD Monitor Kit 56SMKIT

PRODUCT FEATURES

- 5.6" TFT Display
- Dual RCA Video Inputs
- Dual RCA Audio Inputs
- OSD Contrast, Color, Brightness, Tint & Volume Control
- Resolution (960x234)
- Brightness (200 cd/m2)
- Mirror Mode
- Dimensions (6.3"x 5.2"x 1.4")
- Weight (2.1 lbs)

INCLUDES:

Protective Carry Case With Neck Strap,
1.8AH Rechargeable Battery and 12VDC Charger.

B/W Rear Vision System with IR Camera, 7" Monitor & 30' Cable

BW70RVSYS

PRODUCT FEATURES:

- 380 Lines of Resolution
- 6 High Intensity IR Led's
- 2 Channels Audio/Video
- Monitor Power (12VDC 100mA)
- Monitor Dimensions (7.0"x 4.8"X 7.5")
- Monitor Weight (4 lbs)
- Camera Power (12VDC 200mA)
- Camera Dimensions (4.3"x 3" x 3.5")
- Camera Weight (1.1 lbs)
- Optional Second Camera (*see below*)



Add a Second Camera to
this System

BW7CAM



GET QUALITY HIGH RESOLUTION CRT MONITORS

B/W Super High Resolution Monitors

B9M

B/W 9" Monitor

B12M

B/W 12" Monitor

B14M

B/W 14" Monitor

Color High Resolution Monitors

C14M

Color 14" Monitor

C21M

Color 21" Monitor



PRODUCT FEATURES

- Metal Cabinet / Plastic Front
- Looping BNC Video Input
- Looping S-Video Input (Color)
- Looping RCA Audio Input
- Looping Stereo RCA Audio Input (Color)
- Certificates UL, CUL, TUV, FDA, FCC, CE
- Operating Temp (14°F-122°F)

| | SIZE | RESOLUTION | DIMENSIONS | WEIGHT |
|--|----------|------------|------------------------|----------|
| | B9M 9" | 1000 Lines | 8.66"x 9.25"x 9.84" | 10.1 lbs |
| | B12M 12" | 1000 Lines | 12.08"x 11.81"x 11.81" | 15.4 lbs |
| | B14M 14" | 1000 Lines | 13.62"x 12.99"x 14.33" | 19.8 lbs |
| | C14M 14" | 500 Lines | 13.62"x 12.99"x 14.33" | 27.5 lbs |
| | C21M 21" | 500 Lines | 19.29"x 17.72"x 18.50" | 61.6 lbs |

MONITOR CEILING MOUNTS

MMC914

9"-14" For Use with: B9M, B12M

MMC1421

14"-21" For Use with: C14M, B14M

MMC2029

20"-29" For Use with C21M



PRODUCT FEATURES

- Rotates 360°/Tilts 30°
- Holds Up to 45 lbs (MMC914)
- Holds Up to 73 lbs (MMC1421)
- Holds Up to 132 lbs (MMC2029)
- Extends 9.25"-12.25" (MMC914)
- Extends 23"-32" (MMC2029)

MONITOR WALL MOUNTS

MMW1421

14"-21" For Use With C14M, B14M

MMW2029

20"-29" For Use With C21M



PRODUCT FEATURES

- Tilts 30°
- Holds Up to 66 lbs (MMW1421)
- Holds Up to 132 lbs (MMW2029)

MONITOR DOUBLE ARM WALL MOUNT

MMW914H

9"-14" For Use With

B9M, B12M, B14M, C14M




PRODUCT FEATURES

- Holds Up to 31 lbs
- Includes Safety Strap

VISUALIZE THE POSSIBILITIES

WITH THESE SUPER HIGH RESOLUTION
COLOR MONITORS



PRODUCT FEATURES

- VGA Input
- Looping BNC Video Input
- S-Video Input
- Audio Input
- Energy Star Compliant
- VESA Compliant
- OSD Control
- Super Fast 8ms Response Time
- Certificates: Energy Star, UL/CUL, FCC-DOC, TUV/GS, CE, ICES, BSMI, VCCI

LCD1520HG

15" LCD Monitor

LCD1720HG

17" LCD Monitor

LCD1920HG

19" LCD Monitor

| SIZE | RESOLUTION | CONTRAST | BRIGHTNESS | DIMENSIONS | WEIGHT | |
|-----------|------------|-----------|------------|------------|---------------------|----------|
| LCD1520HG | 15" | 1200x760 | 350:1 | 260 cd/m2 | 14.5"x 13.9"x 0.98" | 6.6 lbs |
| LCD1720HG | 17" | 1280x1024 | 400:1 | 300 cd/m2 | 16.5"x 16.5"x 1.18" | 12.9 lbs |
| LCD1920HG | 19" | 1280x1024 | 500:1 | 250 cd/m2 | 16.9"x 16.3"x 1.18" | 13.9 lbs |

LCD PIVOTING MONITOR MOUNT LCDPMT

PRODUCT FEATURES

- Holds Up to 33 lbs
- Meets VESA Standards



LCD TILTING MONITOR MOUNT LCDTMT

PRODUCT FEATURES

- Holds Up to 33 lbs
- Meets VESA Standards



LCD FLUSH MONITOR MOUNT LCDWMT

PRODUCT FEATURES

- Holds Up to 66 lbs
- Meets VESA Standards



Color Triplex Multiplexers

C4TMX

4 Channel

C9TMX

9 Channel

C16TMX

16 Channel

PRODUCT FEATURES

- Alarming Inputs
- Full Triplex Operation
- Electronic Zoom
- On Screen Display



B/W & Color Quads

BQ42

CQ42



PRODUCT FEATURES

- 30 FPS Refresh Rate
- Full Screen/Quad/Auto Display
- Power Supply Sold Separately*

*Recommended Power Supply 12VDC15AMP

Color Quad

CQ41



PRODUCT FEATURES

- 4 Inputs / 2 Outputs (BNC)
- Alarming
- Power Supply Included

SIMPLE SWITCHING SOLUTIONS

COLOR SWITCHER

SS41



PRODUCT FEATURES

- User Adjustable Dwell Time
- 4 Camera Inputs
- Bypass or View Any Camera
- Powered by 110VAC

ALL GLASS ELEMENTS

Varifocal Manual/ Auto Iris Lenses

VL358MI
3.5-8mm Manual Iris, F1.4

VL358AI
3.5-8mm Auto Iris, F1.4

VL2812MI
2.8-12mm Manual Iris, F1.4

VL2812AI
2.8-12mm Auto Iris, F1.4

VL550MI
5-50mm Manual Iris, F1.4

VL550AI
5-50mm Auto Iris, F1.4

VL5100MI
5-100mm Manual Iris, F1.8

VL5100AI
5-100mm Auto Iris, F1.8



infrared

Infrared Varifocal Auto Iris Lenses

VL358IR
3.5-8mm Auto Iris, F1.2

VL2812IR
2.8-12mm Auto Iris, F1.4

VL550IR
5-50mm Auto Iris, F1.6



aspherical

Aspherical Varifocal Auto Iris Lenses

VL308AS
3-8mm Auto Iris, F1.0

VL5100AS
5-100mm Auto Iris, F1.6



Aspherical IR Varifocal Auto Iris Lenses

VL308ASIR
3-8mm Auto Iris, F1.0

VL2812ASIR
2.8-12mm Auto Iris, F1.2

VL850ASIR
8-50mm Auto Iris, F1.3

aspherical + IR

TRUE
day/night
IMAGES



PRODUCT FEATURES

- Aspherical Technology Provides Superior Sensitivity and Resolution
- Super Low Dispersion Glass Elements
- Automatic IR Correction Produces Sharp Images in Varying Lighting Conditions
- Made in Japan
- A "Must Have" For Day/Night Applications

Indoor Mini Dome Wall Mount

MDWMT

PRODUCT FEATURES

- ABS Plastic Construction
- Black Finish
- Dimensions (5.75" x 6.75")
- Weight (0.4 lbs)



FOR USE WITH:

- C540MDVAI Series
- CX580MDVAI Series
- C620MDVAI Series
- C380MDVMI Series
- C480MDVMI Series
- B600MDVAI Series

Vandal Proof Mini Dome Wall Mount

VPMDWMT

PRODUCT FEATURES

- Brushed Aluminum Construction
- Silver Finish
- Dimensions (8" x 6.8")
- Weight (0.75 lbs)



Vandal Proof Mini Dome Wall Mounts with Cable Management

VPMDWMTG

Gooseneck Mount

VPMDPMT

Pendant Mount

PRODUCT FEATURES

- Brushed Aluminum Construction
- Cable Pass-Through Design
- Silver Finish
- 18" Extension (VPMDPMT)



FOR USE WITH:

- C540MDVAIVP Series
- CX580MDVAIVP Series
- C620MDVAIVP Series
- C380MDVMIVP Series
- C480MDVMIVP Series
- B600MDVAIVP Series

Metal Dual Option Camera Mounts

MCM6

Black Camera Mount

MCM6W

Beige Camera Mount

PRODUCT FEATURES

- Wall, Ceiling or T-Bar Mount
- Metal Construction
- Max Load 10 lbs
- 360° Swivel Angle
- 210° Tilt Angle
- Dimensions 6" x 1.5" (Including Base)



Plastic Camera Mount

CWMP

Beige Camera Mount

PRODUCT FEATURES

- Wall Or Ceiling Mount
- 360° Swivel Angle
- 90° Tilt Angle
- Dimensions 6.5" x 3.5" (Including Base)



Outdoor Camera Housings

OCH1

Standard Housing

OCH2

With Heater/Blower

OCHIR75

With 75' IR and Heater/Blower

PRODUCT FEATURES

- Lockable Clasp
- Beige Finish
- 75' IR Range (OCHIR75)
- 12VDC Power (OCHIR75)
- 24VAC Heater/Blower (OCH2)
- Heavy-Duty Aluminum Construction
- Dimensions (13"x 5.2"x 4.1")
- Max Camera Size (3.93"W x 3.14"H x 11.81"L)
- Weight (3.5 lbs)
- Weatherproof



OCH1 / OCH2



OCHIR75

HEAVY-DUTY ALUMINUM CONSTRUCTION



Indoor Wedge Camera Housing ICHWEDGE

PRODUCT FEATURES

- Ideal for Drop Ceiling Applications
- Mounting Hardware Included
- Heavy-Duty Aluminum Construction
- Beige Finish
- Dimensions (4.92W"x 3.93"Hx 13.18"L)
- Max Camera Size (3.93"W x 2.75"Hx 11.02"L)
- Weight (3.35 lbs)

Ceiling J-Mount For Outdoor Camera Housings OCHJMT

PRODUCT FEATURES

- Heavy Duty Metal Construction
- Beige Finish
- 360° Swivel Angle
- 90° Tilt Angle
- Dimensions (13.75"x 11.75")
- Max Load (66.25 lbs)
- Weight (8.5 lbs)



For Use With: OCH1, OCH2 & OCHIR75

Wall Mount For Outdoor Camera Housings OCHWMT

PRODUCT FEATURES

- Heavy Duty Aluminum Construction
- Beige Finish
- 360° Swivel Angle
- 90° Tilt Angle
- Dimensions (11.2"x 3.8"x 3.3")
- Max Load (12 lbs)
- Weight (1.8 lbs)



For Use With: OCH1, OCH2 & OCHIR75

1 In/4 Out Video Distribution Amplifier DA14



PRODUCT FEATURES

- 1,000' Range
- 1 BNC Input
- 4 BNC Video Outputs
- Power Supply Included

Audio Video Amplifier AVA1



PRODUCT FEATURES

- 1,000' Range
- 1 BNC/Audio Input
- 1 BNC/Audio Output
- Power Supply Included

4 Camera Video Amplifier VA4



PRODUCT FEATURES

- 3,200' Range
- 4 BNC Inputs
- 4 BNC Outputs
- Brightness/Sharpness Adjustments
- Power Supply Included

AC/DC Power Converter (800mA) 24VACTO12VDC8



PRODUCT FEATURES

- 24VAC Input Power
- Regulated 12VDC Output (800mA)
- Dimensions (1.6" x 1.0 x 0.7")

Coaxial Surge Protector CSP1



PRODUCT FEATURES

- 100ns Surge Protection Attack Time
- 5AMP Max. Surge Current
- Surge Life 300 Surges (100AMP)

Male DC Power Jack With 12" Leads 12VDCCORD



PRODUCT FEATURES

- Center Pin Positive
- PVC Jacket
- 18 Gauge

Y Power Adapter DCYADAPTER

PRODUCT FEATURES

- Power 2 Cameras With a Single Power Supply
- Or Power 1 Camera and 1 Microphone
- (1) Female to (2) Male Connectors
- Center Pin Positive
- PVC Jacket
- 18 Gauge



Audio/Video Digital TV/Cable TV Modulator MDLAGILE

PRODUCT FEATURES

- View Video on TV Ch. 14-69
- View Video on CATV Ch. 44-134
- BNC Video Input
- RCA Stereo Audio Input
- Dimensions (3.81" x 4.92" x 1.57")
- Power Supply Included



Lapel Microphone MICPA



1000' Twisted Pair Video Baluns

VC1

PRODUCT FEATURES

- 1000' Transmission Range
- Passive, No Power Required
- Uses RJ-45 or Screw Terminals



VC2

PRODUCT FEATURES

- 1000' Transmission Range
- Passive, No Power Required
- Screw Terminal Connection



VCCORD

PRODUCT FEATURES

- 1000' Transmission Range
- Passive, No Power Required
- Screw Terminal Connection
- 15" BNC Cable



16 Channel Passive UTP Hub

VC1616P

PRODUCT FEATURES

- Built in 16 Port Passive Transceiver
- Transmission Range Up to 1,000'
- 16 UTP Inputs to 16 BNC Outputs
- 1U Rack Mountable



16 Channel In / 32 Out Active Hub

VC1632A

PRODUCT FEATURES

- Built in 16 Port Active Receiver
- Transmission Range Up to 3,200'
- 16 UTP Inputs to 32 BNC Outputs
- 1U Rack Mountable



CAT5 Audio/Video Transmission

VCAV1

PRODUCT FEATURES

- 1000' Range
- Transmits Over CAT5
- Impedance Matching



2.4GHZ Wireless System

MW24AVSYS

PRODUCT FEATURES

- 700' Audio/Video Transmission Range
- 2.4GHZ Transmitter/Receiver
- FCC Approved, Part 15
- 4 Channel Selectable
- RCA Audio/Video Connection



24VAC Fused Power Supplies

AC2420VA

20VA Output

AC2440VA

40VA Output

AC2450VA

50VA Output

PRODUCT FEATURES

- Class II, UL Listed
- AC120V Input
- Screw Terminal Connection



OUTDOOR

24VAC Outdoor Power Supply

WX10024UL

100VA Output

PRODUCT FEATURES

- Class II, UL Listed
- AC120V Input
- 100VA Output
- Weatherproof
- Ideal for Use With Outdoor Speed Domes



SINGLE-CAMERA POWER SUPPLIES

12VDC Regulated Power Supplies

12VDC500R

500mA Output

12VDC15AMP

1.5AMP Output

12VDC3AMP

3AMP Output

PRODUCT FEATURES

- Class II, UL Listed
- AC120V Input
- Center Pin Positive



12VDC Rechargeable Battery Kit

12VDC35PACK

3.5AMP Output

PRODUCT FEATURES

- AC 120V Input
- 12VDC 3.5AMP Output
- Includes Trickle Charger
- Center Pin Positive



Multi-Channel 24VAC Power Supplies

AC411UL

4 Camera, 100VA Output

AC421UL

4 Camera, 200VA Output

AC811UL

8 Camera, 100VA Output

AC821UL

8 Camera, 200VA Output

AC1621UL

16 Camera, 200VA Output


AC1641UL

16 Camera, 400VA Output

PRODUCT FEATURES

- Removable Glass Fuses
- Meets Class II Requirements
- UL Listed

MULTI-CAMERA POWER SUPPLIES



REMOVABLE GLASS FUSES

Multi-Channel 12VDC Power Supplies

DCR441UL

4 Camera, 4 AMP Output

DCR461UL

4 Camera, 6 AMP Output

DCR481UL

4 Camera, 8 AMP Output

DCR841UL

8 Camera, 4 AMP Output

DCR881UL

8 Camera, 8 AMP Output

DCR1681UL

16 Camera, 8 AMP Output

DCR1612UL

16 Camera, 12 AMP Output

PRODUCT FEATURES

- Removable Glass Fuses
- Meets Class II Requirements
- UL Listed



Bulk 2 Conductor 18AWG Power Cable



182500W
White 500'

1821KW
White 1000'

Bulk RG59 Video Cable



RG59500B
Black 500'

RG59500W
White 500'

RG591KB
Black 1000'

RG591KW
White 1000'

Bulk Siamese Video Cable (18/2-RG59)



RG59ZIP500B
Black 1000'

RG59ZIP500W
White 500'

RG59ZIP1KB
Black 1000'

RG59ZIP1KW
White 500'

Bulk RG6 Video Cable



RG61KB
Black 1000'

Bulk CAT5E Cable (4 PAIR)



CAT5E1KG
Gray 1000'

BNC Connectors/Adapters



BNCCRIMP
BNC Male 2-Piece Crimp Connector



BNCTWIST
BNC Male Twist on Connector



BNCFTORCAM
BNC Female to RCA Male Adapter



BNCMTORCAF
BNC Male to RCA Female Adapter



BNCSPICE
BNC Female to Female Adapter



BNCT
BNC Male to (2) BNC Female Adapter



PRODUCT FEATURES

- Ideal for CCTV Applications
- Precision Engineered
- Cable Type RG59/U
- Easy Connection
- Zinc Body
- Copper Contact

Pre-Made BNC to BNC Cables

CBL3BNC

3' Length

CBL6BNC

6' Length

CBL25BNC

25' Length

CBL50BNC

50' Length

CBL100BNC

100' Length

PRODUCT FEATURES

- RG59/U Cable with BNC Connectors
- Solid Copper Core
- 95% Copper Shielding
- PVC Jacket



Pre-Made Video & Power Cables

CBL25PVB

Black 25' Length

CBL25PVW

White 25' Length

CBL50PVB

Black 50' Length

CBL50PVW

White 50' Length

CBL100PVB

Black 100' Length

CBL100PVW

White 100' Length

PRODUCT FEATURES

- Video/Power Cable
- Male to Female Power Connector
- Center Pin Positive
- BNC to RCA Video Connector
- 2 RCA to BNC Adapters



CAPTURE VIDEO AS IT HAPPENS. IN REAL TIME.

8 & 16 Channel
Real-Time DVR's

RT8CD/RT16CD Series

- Up to 480 FPS Real-Time Recording
- Up to 2.25 TB Internal Storage
- Full Triplex Operation
- Built-in CD-R/W & USB Offload



ARM YOUR WORLD...

**ARM
ELECTRONICS**

8860 INDUSTRIAL AVE., SUITE 140
ROSEVILLE, CA 95678