

# PORTÉGÉ 3490CT

The Portégé® 3490CT is the ultimate statement in mobile computing with its Pentium® III power, large high resolution colour display, long battery life and easy functionality all packed into an ultra thin lightweight body finish in sleek magnesium.

With head turning style and work burning performance, the Portégé® 3490CT is the perfect tool for the travelling executive ready to succeed in the new world.

# PORTÉGÉ® 3490CT MEMORY DISPLAY HARD DISK MODEM WIN98/WIN2000/WIN NT4

# **FUNCTIONALITY**

- Pentium® III 700MHz processor with low voltage for long battery life
- Option for up to 9 hours battery life
- International modem built-in - no dongles
- USB floppy diskette drive
- 2 x Type II PC Card slots
- Integrated monitor port
- Bundled LAN replicator

# RELIABILITY

- Durable magnesium design
- 3 year parts and labour warranty

# **MULTIMEDIA**

- · Optional multimedia expansion and DVD capability
- · Inbuilt speaker and microphone
- Brilliant 11.3 poly-silicon active TFT colour display
- High Resolution XGA 1024 x 768

It's a whole new world out there.



# PORTÉGÉ 3490CT

# **PORTÉGÉ<sup>®</sup> 3490CT ULTRA SLIM PORTABLE**

# PROCESSOR

Mobile Intel® Pentium® III processor featuring Intel SpeedStep Technology 700MHz (1.35V) with 256KB Level 2 integrated on die Integrated co-processor 32KB internal cache Data/Address Bus Width: 64-bit/32-bit 100MHz Processor System Bus

# MEMORY

128MB on board expandable to 256MB One available memory slot (for use with 64MB or 128MB memory module)

APM V1.2, ACPI V1.0b, PnP V1.0a, VESA V2.0, DPMS, DDC2B, SM Bios V2.3, PCI BIOS V2.1

## SYSTEM ARCHITECTURE

PCI Bus V2.2: Intel 440MX System Chipset

# STORAGE DEVICES

20GB\* Hard Disk

Supports PIO Mode 4, Ultra DMA Mode 2, Multiword DMA mode 2

Accommodates 9.5mm height, 2.5" hard drive 13 ms average access time Enhanced IDE (ATA-4) interface, Service removable External USB 1.4MB 3.5" Floppy Diskette Drive

S3 Savage IX graphics controller 8MB SGRAM Internal Video Memory 128-bit BitBLT engine with Direct3D support

# DISPLAY

Polysilicon TFT Colour LCD (11.3" diagonal) Up to 16 million colours at 1024 x 768 resolution

# **EXTERNAL COLOUR SUPPORT**

16M colours: 1024x768, 800x600, 640x480 @ 60/75/85Hz Non Interlaced, simultaneous mode 64K colours: 1024x768, 800x600, 640x480 @ 60/75/85Hz Non-Interlaced, simultaneous mode 280x1026 @ 60/75Hz Non-Interlaced, 1600x1200 @ 60Hz Non-Interlaced

256 colours: 1024x768, 800x600, 640x480 @ 60/75/85Hz Non-Interlaced, simultaneous mode 280x1024 @ 60/75Hz Non-Interlaced, 1600x1200 @ 60Hz Non-Interlaced

# KEVBOARD

85 keys with 12 function keys 2mm key stroke Dedicated Windows® key Integrated AccuPoint™ pointing device with programmable scroll function

YAMAHA YMF743, 16-bit stereo Compatibility: Windows Sound System V2.0 and Sound Blaster Pro compatible MIDI playback 3D sound support Direct Sound, Direct 3D Sound, Direct Music Full duplex sound support, 64 voices

Headphone support (Stereo) External microphone port Built-in speaker Built-in microphone

# COMMUNICATIONS

Integrated International V.90 modem\*\* RJ-11 modem port

### **EXPANSION**

Two PC Card slots supporting either:

2 x Type II (5mm) PC Cards or 1 x Type III (10.5mm) 32-bit CardBus Compatible

PCMCIA R2.01, PC Card 16, CardBus One expansion memory slot available

(for use with 64MB or 128MB memory module)

SVGA video port

Fast infrared port (4Mbps, IrDA V1.1 compliant)

Universal Serial Bus (USB) port

RJ-11 modem port

Serial PCI port - for use with LAN Port Replicator, I/O Adapter and Multi-Media Port Replicator

# LAN PORT REPLICATOR (BUNDLED)

Provides serial, parallel, SVGA, PS/2™ mouse/keyboard, USB, 10/100 Ethernet, headphone line-out and

# MULTIMEDIA PORT REPLICATOR (OPTIONAL)

Provides SelectBay $^{\text{IM}}$ , 1 x Type II PC Card slot, serial, parallel, SVGA, PS/ $2^{\text{IM}}$  mouse/keyboard, USB, 10/100 Ethernet, headphone line-out and power ports

262mm x 231mm x 20mm\*\*\*

1.5KG (with main 6-cell battery)

# POWER SUPPLY

45W External AC Adapter 100-240V input voltage 50-60Hz frequency

# BATTERV

Rechargeable, removable Lithium Ion battery (10.8V, 3000mAh, 6-cell) 2.5+ hours battery life\*\* 3 hours recharge time (off) ACPI V1.0b support

Battery life may vary depending on applications, power management settings and features utilised. Recharge time varies depending on usage

SM V2.3 BIOS support with asset tag capability ACPI V1.0b power management

# SOFTWARE COMPATIBILITY

Window 98SF

Microsoft Windows® NT4/2000

# **SECURITY**

Power-on password HDD access password Keyboard lock

CPU Serial Number Security (using SVPW utility) Setup Security (using SVPW utility)

Screen Blank Cable lock slot

# WARRANTY

3 Year domestic parts and labour warranty with free courier pick up and delivery service

1 Year international parts and labour warranty Warranty service is available through authorised Toshiba Procare resellers

# **ENVIRONMENTAL SPECIFICATIONS**

Operating Temperature: 5° to 35°C Non-operating: -20° to 65°C

Operating Thermal Gradient: 15°C per hour maximum 20°C per hour maximum Non-operating: Operating Rel. Humidity: 20% to 80% non-condensing 10% to 90% non-condensing Non-operating:

Operating Altitude\*: -60m to 3.000m Non-operating: -60m to 10,000m

Operating Shock: 10G Non-operating: 60G Operating Vibration: 0.5GNon-operating: 1G

# STANDARD PACKAGING INCLUDES

Portégé® 3490CT SYSTEM 20GB hard disk drive Lithium Ion 6-cell battery External USB floppy diskette drive LAN Port Replicator

AC Adapter Online user Guide

# FEATURED CONFIGURATION

Part Number

700MHz, 11.3 TFT, 128MB, 20GB, Modem, LAN, Win 98 PP349A-6PV83

700MHz, 11.3TFT, 128MB, Modem, PP349A-6PV86

LAN, WIN NT4/W2K

# **ACCESSORIES** KTT-MD100/641

Kingston 64MB Memory Kingston 128MB Memory AC Adapter Universal AC Adapter (70W) KTT-MD100/1281 PA3035E-1ACA PA143F PA3038U-1BAL Main Battery (6 cell) High Capacity Battery
Battery Recharger
6GB HDD for Multimedia Port Replicator PA3039U-1BAL PA2513U PA3012U-1H06

PA3027U-1H12 12GB HDD for Multimedia Port Replicator 20GB HDD for Multimedia Replicator HDD Adapter (required for HDD) CD-ROM for Multimedia Port Replicator PA3056U-1H2O PA302OU-1OTR PA3015U-1CDD PA3014A-2DVD DVD Drive for Multimedia Port Replicator USB Floppy Disk Drive PA3043U-1FDD PA3040U-1PRP LAN Port Replicator

PA3042U-1DST Multimedia Port Replicator PA3041U-1PRP NW24XCD KENS60648 I/O Adapter PC-Card External 24x CD-ROM Security Cable Lock with Key Lock DEFCON LOCK DEFCON1 Defcon Security Cable Lock with Combination Personal Security Device

PA350/Tosh Auto/Air Power Adapter NWMOSSU Silver Optical USB Mini-Mouse Silver USB Mini-Mouse with trackball 18-Key Slimline numeric keypad Black USB Mini Hub NWMSSUP PAUK001Y001 PAO6OU

NWDVD01 NWUNMIS PC-Card external DVD/CD-ROM Monitor Stand Wireless LAN PC Card PA3064U-1PCC Wireless LAN Access Point PC Card Fingerprint Reader Slim-line top loading Carry Bag PA3065U-1FTC PA3066U-1PCC Tufapak Port Note-Prem Top loading Koskin Carry Bag Koskin Carry Bag Leather Carry Bag

Please direct all enquires to:



Toshiba (Australia) Ptv. Limited ACN 001 320 421 NB: \*GB indicates one billion bytes when referring to hard disk capacity. Accessible capacity may vary. \*\*Australia, New Zealand, Austria, Belgium, Canada, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK and USA. \*\*\*Thickness may vary at certain points on the system \*\*\*Battery Life depends on usage and is measured using PC Magazine BatteryMark. # Relative to sea level. Specifications subject to change without notice. Toshiba is not responsible for errors in typography or photography. Trademarks as indicated are registered trademarks and are the property of the respective owners. Battery is eligible for 12 months domestic warranty only. Toshiba Australia Information Systems Division 2/01.

