

Part Number: 9463NH

ControlBus™ Blue Hose® Industrial Twinax



Product Description

20 AWG, Stranded (42 x 36) TC Conductors, Polyethylene Insulation, Overall Beldfoil® + 85% TC Braid Shielding, Blue Sunlight-Resistant FRNC Jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Eca
Suitable Applications:	Twinaxial instrumentation and computer cable; For data transmission applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
20	7x28	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1
Conductor Size:	20 AWG

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance
Polyethylene	1.96 mm	0.05 mm

Color Chart

Number	Color
Pair 1	Clear & Blue

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Thickness of Foil	Drainwire Material	Drainwire AWG
Tape	Aluminum/Polyester	Z-fold®		9 / 23 µm	TC - Tinned Copper	AWG20/7
Braid	TC - Tinned Copper		55 %			

Outer Jacket Material

Material	Color	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	Blue (like RAL 5012)	6.35 mm	0.89 mm

Construction and Dimensions

Cabling

Description	Filler
1 pair and 2 fillers twisted to cable core	Polyethylene (2x) (Clear, 1.32 mm)

Electrical Characteristics

Conductor DCR

Max. DCR Unbalance	Nominal Conductor DCR	Nominal Outer Shield DCR
2.53 %	31.2 Ohm/km	13.5 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Shield
64.6 pF/m	118.1 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance
N/A	78 Ohm

Delay

Nominal Velocity of Propagation (VP) [%]
66 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)
1 MHz	1.97 dB/100m
10 MHz	6.89 dB/100m
50 MHz	11.81 dB/100m
100 MHz	24.61 dB/100m
200 MHz	36.09 dB/100m
400 MHz	52.49 dB/100m

Voltage

Voltage Rating [V]
300 V

Temperature Range

Installation Temp Range:	-15°C To +80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Oil Resistance:	ASTMD741
Min Bend Radius During Installation:	63.5 mm

Standards

CPR Euroclass:	Eca
Other Specification:	BS 7655 section 6.1 table 1, LTS 3

Applicable Environmental and Other Programs

EU RoHS Compliance Date (yyyy-mm-dd):	2005-01-01
---------------------------------------	------------

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-3-24
Amount of Halogen acc. to IEC 60754-1 & EN50267-1:	Zero

Part Number

Variants

Item #	Color
9463NH.001000	Blue
9463NH.00152	Blue
9463NH.00305	Blue
9463NH.00500	Blue

History

Revision Number:	5
------------------	---

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.