



Part Number: 9842NH

RS485, #24-2pr, PO, O/A Foil+Braid, LSZH Jkt, 120Ω

Product Description

Computer EIA RS-485 Cable, 24 AWG stranded (7x32) tinned copper conductors, polyethylene insulation, 2 twisted pairs, overall Beldfoil® (100% coverage) + tinned copper braid shield (90% coverage), 24 AWG stranded tinned copper drain wire, LSZH jacket

Technical Specifications

Product Overview

Environmental Space:	Indoor - Euroclass Dca
Suitable Applications:	Instrumentation and computer cable; For EIA RS-485 data transmission applications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
24	7x32	TC - Tinned Copper	2

Conductor Count:	4
Total Number of Pairs:	2
Conductor Size:	24 AWG

Insulation

Material	Nominal Diameter	Diameter +/- Tolerance	Nominal Wall Thickness
Polyethylene	1.73 mm	0.05 mm	0.02 in

Color Chart

Number	Color
Pair 1	White/Blue & Blue/White
Pair 2	White/Orange & Orange/White

Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Thickness of Foil	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum/Polyester	Z-fold®	100 %	9 / 23 µm	TC - Tinned Copper	AWG24/7	7x32 mm
Braid	2	TC - Tinned Copper		90 %				

Outer Jacket Material

Material	Color	Nominal Diameter	Nominal Wall Thickness
LSZH / FRNC (UV stabilised)	Chrome (like RAL 7037)	8.65 mm	0.9 mm

Construction and Dimensions

Stranding

Lay Direction	Twists
Left Hand	12 twist/ft

Cabling

Description	Filler
2 pairs and 2 fillers twisted to cable core	Polypropylene (2x) (White, 2.87 mm)

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
78.7 Ohm/km	7.2 Ohm/1000ft

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
42 pF/m	75.5 pF/m

Impedance

Frequency [MHz]	Nominal Characteristic Impedance
1	120 Ohm

High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
0.6 MHz	1.97 dB/100m

Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
66 ns/100m	1.54 ns/ft	66 %

Current

Element	Max. Recommended Current [A]
Conductor	2.1 A

Voltage

UL Voltage Rating	Voltage Rating [V]
300 V RMS	300 V

Temperature Range

Installation Temp Range:	-15°C To +80°C
UL Temp Rating:	80°C
Storage Temp Range:	-45°C To +80°C
Operating Temp Range:	-20°C To +80°C
Operating Temp Range (Flexible Install):	-15°C To +80°C
Operating Temp Range (Fixed Install):	-45°C To +80°C

Mechanical Characteristics

Oil Resistance:	IEC 60811-404
Bulk Cable Weight:	49 lbs/1000ft
Max Recommended Pulling Tension:	395 N
Min Bend Radius During Installation:	86.5 mm
Min Bend Radius/Minor Axis:	3.25 in

Standards

CPR Euroclass:	Dca-s2,d2,a1
CENELEC Compliance:	EN 50290-2-27

Applicable Environmental and Other Programs

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2012-05-10
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Non-Halogenated:	Yes

Flammability, LSOH, Toxicity Testing

ISO/IEC Flammability:	IEC 60332-3-24
-----------------------	----------------

Amount of Halogen acc. to IEC 60754-1 & EN50267-1: Zero

Plenum/Non-Plenum

Plenum (Y/N): No

Part Number

Variants

Item #	Color	Footnote
9842NH.02500	Black	
9842NH.022500	Black	
9842NH.02520	Black	
9842NH.001000	Chrome	
9842NH.00152	Chrome	
9842NH.00305	Chrome	
9842NH.00500	Chrome	
9842NH 0601000	Chrome	C
9842NH 060500	Chrome	
9842NH.002500	Chrome	
9842NH 0601000	Chrome	C
9842NH.011000	White	
9842NH.01305	White	

Footnote: C - CRATE REEL PUT-UP.

History

Revision Number: 8

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.