



For more Information
please call

1-800-Belden1



General Description:

14-conductor EFP and ENG camera cable, foam polyethylene (coax) and PVC (pairs and conductors) insulation, overall PVC jacket.

Coax

Physical Characteristics

Conductor

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
2	22	7x30	BC - Bare Copper	0.030

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FPE - Foam Polyethylene	0.146

Inner Shield

Inner Shield Material:

Type	Inner Shield Material	% Coverage (%)
Braid	BC - Bare Copper	95

Inner Jacket

Inner Jacket Material:

Inner Jacket Material	Nom. Dia. (in.)
PVC - Polyvinyl Chloride	0.242

Inner Jacket Color Code Chart:

Number	Color
1	Black
2	Black w/Hash Marks

Applicable Specifications and Agency Compliance Applicable Standards & Environmental Programs

EU CE Mark: No

RG Type: 59/U

Electrical Characteristics

Nom. Characteristic Impedance:

Impedance (Ohm)
75

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.300

Nominal Velocity of Propagation:

VP (%)
78.000

Nominal Delay:

Delay (ns/ft)
1.300

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
15.600

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
2.540

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	0.300

2.000	0.600
10.000	1.000
50.000	2.300
100.000	3.200

Max. Operating Voltage - Non-UL: 300 V RMS

Twisted Pair

Physical Characteristics

Conductor

AWG:

# Pairs	AWG	Stranding	Conductor Material	Dia. (in.)
5	22	7x30	TC - Tinned Copper	0.030

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PVC - Polyvinyl Chloride	0.054

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG	Stranding	Dia. (in.)	Conductor Material
22	7x30	0.030	TC - Tinned Copper

Inner Jacket

Inner Jacket Color Code Chart:

Number	Color
1	Black and Red
2	Black and White
3	Black and Green
4	Black and Blue
5	Black and Yellow

Electrical Characteristics

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
16.700

Multi Conductor

Physical Characteristics

Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (in.)
2	16	26x30	TC - Tinned Copper	0.060

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
PVC - Polyvinyl Chloride	0.092

Insulation Color Code Chart:

Number	Color
1	Black
2	White

Electrical Characteristics

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
31.100

Nominal Velocity of Propagation:

VP (%)
62.000

Nominal Delay:

Delay (ns/ft)
1.640

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
4.400

Nom. Inner Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
12.500

Max. Operating Voltage - Non-UL:

Voltage	Description
300 V RMS	Pairs
300 V RMS	Conductors

Physical Characteristics (Overall)

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.585 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +75°C
Non-UL Temperature Rating:	75°C
Bulk Cable Weight:	186 lbs/1000 ft.
Max. Recommended Pulling Tension:	337 lbs.
Min. Bend Radius/Minor Axis:	5.900 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes
Sunlight Resistance:	Yes

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9171 0601000	1,000 FT	193.000 LB	CHROME	C	5 SHLD PR#22,2#16,2 COAX
9171 060500	500 FT	97.500 LB	CHROME	C	5 SHLD PR#22,2#16,2 COAX

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 0 Revision Date: 02-16-2009

© 2016 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.