


## H155A00

Part Number: H155A00

COAX RF H155 PVC



### Product Description

COAX RF H155 PVC

### Product Specifications

#### Application

Application 1:	50 Ohm low loss coaxial transmission cable designed according European Standard EN 50117-1
Application 2:	Operating frequencies between 5 and 6000 MHz

### Technical Specifications

#### Bend Radius

Min Bend Radius (W/o Pulling Strength):	60 mm
---	-------

#### CCB-Sub-Crush Resistance

Crush Resistance:	Max. 1% (load of 700N) N
-------------------	--------------------------

#### CCB-Sub-Material

Min Elongation at Break of Jacket:	150 MPa
Min Tensile Strength of Jacket:	12.5 lbs

#### EMEA Standard

CENELEC Compliance:	EN 50117-1, EN 50117-2-4 and EN 50290-2-20
---------------------	--

#### Environmental Characteristics

Operating Temp Range:	-15 to +70 °C
Storage Temp Range:	-15 to +70 °C
Installation Temp Range:	-5 to +50 °C

## General Electrical Parameters

General Electrical Parameters Header:	Test methods in accordance with EN 50117-1
Min Insulation Resistance:	10000 mOhm/1000ft

## History

Revision Date:	2013-06-13
Revision Number:	2

## Safety

ISO/IEC Flammability:	IEC 60332-1-2
-----------------------	---------------

## Stripping Performance

Adhesion Dielectric:	5-50 at 25 mm
----------------------	---------------

## Use

Max Recommended Pulling Tension:	100 lbs
----------------------------------	---------

### Impedance:

Nominal Characteristic Impedance		
50 mOhm/ft	3 Ohm	Min. 40 dB

### Conductor DCR:

Max. Conductor Loop	Max. Inner Shield DCR	Max. Shield DCR
32.4 Ohm/1000ft	15.4 Ohm/km	17 Ohm/km

### Delay:

Nominal Velocity of Propagation (VP)	Velocity of Propagation Tolerance
80 ns/100m	2 %

### Voltage:

Voltage Test Dielectric
-------------------------

2 kV DC

### High Freq:

Element	Frequency [MHz]	Min. RL (Return Loss)
	5 - 30 MHz	20 dB
	30 - 470 MHz	20 dB
	470 - 1000 MHz	18 dB
	1000 - 2000 MHz	16 dB
	2000 - 3000 MHz	15 dB
for information only	3000 - 6000 MHz	15 dB

In each frequency band, 3 peak values up to 4 dB lower are allowed

### Screening:

Frequency	Min. Screening Attenuation
30 - 1000 MHz	85

### Capacitance:

Capacitance Tolerance	Nominal Capacitance Conductor to Shield
3 pF/m	84 pF/m

### High Frequency (Nominal/Typical):

Element	Frequency (MHz)	Nom. Insertion Loss
	5 MHz	2.5 db/100m
	50 MHz	6.9 db/100m
	100 MHz	9.1 db/100m
	230 MHz	13.4 db/100m
	400 MHz	18 db/100m
	800	26.1 db/100m
	862	27.3 db/100m
	1000	29.6 db/100m
	1350	34.9 db/100m
	1750	40.3 db/100m

	2150	46 db/100m
	2400	49.1 db/100m
	3000	56.3 db/100m
	3600	62.9 db/100ft
	4200	69.1 db/100ft
	4800	75.1 db/100ft
	5400	80.8 db/100ft
	6000	86.5 db/100ft

Max. attenuation 10% higher

#### Insulation:

Element	Type	Material	Nominal Diameter	Diameter +/- Tolerance
	Dielectric	Foamed Polyethylene	3.9 mm	0.15 mm

Centricity min. 85%

#### Outerjacket 1:

Material	Nominal Diameter	Diameter +/- Tolerance
PVC	5.4 mm	0.2 mm

#### Conductor:

Stranding	Material	ConstructionNXD	Nominal Diameter	Diameter +/- Tolerance
Stranded	Bare copper	19x0.28 mm	1.41 in	0.03 mm

#### Outershield 1:

Type	Layer	Material	Coverage	Min. Overlap	Nominal Diameter	Diameter +/- Tolerance	Coverage +/- Tolerance
Tape	1	Aluminum / Polyester / Aluminum		2 mm			
Braid	2	Tinned copper	80 %		4.5 mm	0.25 mm	5 %

## Product Variants

Part Number	Color	Put-Up Type	Length
H155A00.001000	GRAY	Reel	1000 m
H155A00.00250	GRAY	Reel	250 m
H155A00.00252	GRAY	Reel	252 m
H155A00.00500	GRAY	Reel	500 m
H155A00.00505	GRAY	Reel	505 m
H155A00.009999	GRAY	Reel	499 m
H155A00.00B100	GRAY	Flat Box	100 m
H155A00.00B50	GRAY	Flat Box	50 m
H155A00.099999	GRAY	Reel	999 m

© 2015 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.