

AXIS T90C Fixed Dome IR-LED

Vandal-resistant illuminators for outdoor environments

AXIS T90C10 and AXIS T90C20 are infrared, vandal-resistant illuminators for outdoor versions of AXIS P33 Network Cameras. Providing fixed angle illumination, they enable the camera to deliver high quality images in complete darkness. With eight high-power LEDs that provide a wide angle light beam, the fixed dome camera gets a viewing range of 20–30 m (67–98 ft), depending on environment and installation. They have a built-in photocell and come with a pre-mounted 5 m (16 ft) cable. The IP66- and NEMA 4X-rated AXIS T90C10 and AXIS T90C20 can be used in severe outdoor conditions and extreme temperatures.

- > **Choice of AC/DC or PoE power input**
- > **High-intensity LEDs**
- > **Easy to install**
- > **Long life and low power consumption**



AXIS T90C Fixed Dome IR-LED

General	
Angle	Angle of beam: 180° Primary beam (max effect): 120°
Distance	20–30 m (66–98 ft) depending on environment and installation
Control technology	Controlled by an adjustable visible light sensor
Type	850 nm semi-covert
Casing	Color: White NCS S 1002-B IP66- and NEMA 4X-rated Vandal-resistant aluminum casing
Power	AXIS T90C10: 18–56 V DC input Consumption: 13 W AXIS T90C20: Power over Ethernet (IEEE 802.3af)
Operating conditions	-40 °C to 55 °C (-40 °F to 131 °F)
Approvals	EN 55022 Class B, EN 55024, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22, EN 60950-1, EN 60950-22, conforming to UL 60950-1 and UL 60950-22
Dimensions	130 x 256 x 47 mm (5.1 x 11 x 1.8 in)
Weight	700 g (1.5 lb)
Included accessories	AXIS T90C10: Pre-mounted 5 m (16 ft) power cable AXIS T90C20: Pre-mounted 5 m (16 ft) network cable
Optional accessories	AXIS T90C10: AXIS T90C10 Mains adaptor
Warranty	3-year warranty, see axis.com/warranty

Environmental responsibility:

axis.com/environmental-responsibility