

vivopay[®] Kiosk II[™]

Flexible Integration of Contactless Payments

The ViVopay Kiosk II is a flexible stand-alone contactless reader comprised of a compact controller module and an RFID antenna module packaged individually giving equipment manufacturers flexibility to integrate contactless payment functionality with their host systems. The design approach allows the controller module to be easily installed within minimal footprint and effort in customer-facing locations.

The ViVopay Kiosk II is certified with most contactless payment programs such as MasterCard[®] MCL, AMEX[®] Expresspay, Visa[®] VCPS and Discover[®] DPAS, as well as Apple Pay and Android Pay.

The ViVopay Kiosk II also supports contactless ticketing functionality such as what which is used in most transit systems worldwide as well as NFC mobile phone payments and promotions. Its powerful ARM processor and remote download capability allows for future scalability and updates. Operators can rest assured that the investment of today will support the developments in contactless payments of the future.



Features and Benefits:


- **Contactless:** Compatible with ISO/IEC 14443 Type A & B, MiFare[®], and NFC.
- **Applications:** Retail drive-thru, ticketing machines, transit turnstiles/fare collection systems, reload machines for transit system, airport self check-in, parking ticket validation/payment boxes, parking meters and many other indoor and outdoor applications.
- **Flexibility:** Controller module and RFID antenna module packaged individually give equipment manufacturers flexibility to integrate contactless payment functionality with their host systems.
- **Remote Download:** Post-deployment firmware updates via remote download without requiring additional hardware or device resetting.
- **Speed:** Enables quick transactions improving vending machine-based sales.



Square Bezel Antenna

Small Footprint for applications with limited space or flush mounting.

→ Contactless NFC



Angled Bezel Antenna

For a more integrated application and increased tamper resistance.

→ Contactless NFC

Hardware

Processor:	ARM Processor
Audio-Visual:	Beeper and LEDs
Input Power:	7.5 - 36 VDC

Contactless Transactions

Interface:	13.56MHz ISO 14443 Type A/Type B, MiFare
Payment Applications*:	AMEX ExpressPay, Discover DPAS, MasterCard MCL, Visa VCPS, and PBOC
Mobile Payments:	Android Pay, Apple Pay, and other mobile wallets

Connectivity

Interface:	RS-232, USB
Firmware upgrades:	Remote firmware download

Physical Dimensions

Square Bezel Antenna

Height (X):	75 mm (2.95 inches)
Length (Y):	60 mm (2.36 inches)
Width (Z):	16.8 mm (0.66 inches)
Weight:	0.30lb.

Angle Bezel Antenna

Height (X):	96.2 mm (3.787 inches)
Length (Y):	82.3 mm (3.24 inches)
Width (Z):	16.8 mm (0.66 inches)
Weight:	0.35lb.

Controller

Height (X):	105 mm (4.13 inches)
Length (Y):	76.2 mm (3.00 inches)
Width (Z):	22.5 mm (0.88 inches)
Weight:	0.15lb.

Environmental

Operating Temp:	-13F to +158F (-25C to +70C)
Storage Temp:	-40F to +185F (-40C to +85C)
Operating Humidity:	10% to 90% non condensing
Other:	Weather-proofed UV-rated plastic enclosure

United States Sales Office

Corporate Headquarters

10721 Walker Street
Cypress, CA 90630
Phone: (714) 761-6368
Toll Free: (800) 984-1010
Fax: (714) 761-8880
sales@idtechproducts.com

International Sales Offices

Asia

+866-3-496-6988 (Taiwan)
asia@idtechproducts.com.tw

Canada

+450-465-5261
robertop@idtechproducts.com

South America

+55-11-3079-2255
internationalsales@idtechproducts.com

Europe

Germany & United Kingdom
emea@idtechproducts.com

ISO 9001 Certified



Antenna Module

ViVOpay Kiosk II design approach allows controller module to be installed inside host system and antenna to be installed with minimal footprint in a customer-facing location.



Controller Module

* Application specifications depend on hardware & software configuration.