
RM-2443 Series

Quad 4.3" HD/SD-SDI/Analog Video Monitors




Full feature set, cost effective, reliable quad 4.3" video monitor with inscreen audio level meters. vectorscope and waveform

2HD Rear Panel



HD Rear Panel



The RM Series is a full-featured, low-cost range of in-rack HD/SD-SDI and CVBS video monitors ideal for the many feeds in mobile trucks, news and transmission control rooms, duplication, and post production applications.

These tilting monitors come standard with in-monitor level metering, selectable video waveform and vectorscope, safe and title markers, labeling, tally, timecode, video format, and built-in color bars, as well as familiar CRT-style picture controls and an intuitive on-screen configuration menu.

Input signals are automatically detected and up to 8 of the 16 audio channels embedded in an HD/SD-SDI bitstream may be selected for visual monitoring on 8 on-screen bar graph style level meters. A headphone jack provides audible stereo monitoring of selected left and right channels.

Each of the four high-resolution LCD screens display high-definition or standarddefinition video at either 16:9 or 4:3 aspect ratio. Parameters are selected and adjusted using an on-screen display menu.

Benefits:

- On-screen level meters provide confidence audio monitoring
- Tally and on-screen labeling provide quick and easy signal identification
- CRT-style image controls allow video image enhancement for each screen individually
- User defined hot key functionality provides either H/V delay, underscan, on-screen display, and more

Features:

- In-picture waveform, and vectorscope display
- Labelling, tally, timecode, detected video format, safe area and title markers display
- On-screen image calibration controls
- Gamma color calibration
- Built-in color bars
- User-defined function buttons
- Intuitive on-screen menu
- Headphone output



Order Part Numbers

RM-2443W-2HD: 8001-0160 (2 HD/SD-SDI Inputs per screen; No Outputs) RM-2443W-HD: 8001-0050 (1 HD/SD-SDI Input per screen; 1 Output)











RM-2443 Series

Quad 4.3" HD/SD-SDI/Analog Video Monitors

RM Series In-screen Features



Specifications -HD -2HD

| Display Type | Active color matrix amorphous 4.3", LCD TFT screens | |
|---------------------------------|--|--|
| Display Size | 4.3" Diagonal | |
| Resolution | 480 x 270 | |
| Aspect Ratio | 16:9 native 4:3 selectable | |
| Active Viewing Angle | 160°H x 160°V | |
| Active Viewing Area | 3.75" H x 2.12" V (96 mm H x 53 mm V) | |
| Luminance | 165 cd/m^2 | |
| Colors | 16.7 million | |
| Contrast | 400:1 | |
| Pixel Pitch | 0.198 mm H x 0.198 mm V | |
| Pixel response | <30 ms off-on-off (black to white to black) | |
| Inputs | 4 Auto-Sensing HD/SD-SDI, CVBS Inputs on BNC (1 per screen) GPI & RS-485 for UMD/Tally on RJ-45 | 8 Auto-Sensing HD/SD-SDI, CVBS Inputs on BNC (2 per screen) GPI & RS-485 for UMD/Tally on RJ-45 |
| Outputs | 4 HD/SD-SDI Outputs on BNC (1 per screen) RS-485 loop out UMD/Tally on RJ-45 1 Headphone | RS-485 loop out UMD/Tally on RJ-45 1 Headphone |
| Space Requirements | 2RU in a standard 19" rack | |
| Accessories Included | AC power cord | |
| Power Connector | AC power adapter (100-240VAC to 12 VDC) | |
| Power Requirements | Power to the unit connects to mains power (100 to 240 VAC ± 10%, 50/60Hz) | |
| Power Consumption | 10W | |
| Dimensions (H x W x D) | 3.5" x 19" x 2.4" [89 mm x 486 mm x 61 mm] | |
| Shipping Weight / Net Weight | 8 lbs (3.63 kg) / 5 lbs (2.3 kg) | |

View complete list of specifications online at wohler.com

Wohler Technologies, Inc. Worldwide Headquarters 31055 Huntwood Avenue Hayward, CA 94544 USA Phone: +1 510 870 0810 Email: sales@wohler.com Wohler Technologies/APAC 45/F, The Lee Gardens 33 Hysan Avenue Causeway Bay, Hong Kong

Causeway Bay, Hong Kong Phone: +852 8199 0563 Email: sales@wohler.com Wohler Technologies/EMEA Suite 3, Medaxon House Mill Mead, Staines TW18 4UQ, UK Phone: +44 (0) 2071 935507

Email: sales@wohler.com

Infinite Possibilities. One Wohler.