

# Big Digit Hygro-Thermometers

Simultaneous display of Temperature and Humidity

## Features:

- Attractive design for desktop or wall mounting
- Large LCD displays of Temperature and Humidity
- Max/Min memory with reset for Temperature and Humidity
- Switchable °C or °F temperature units
- Complete with built-in tilt stand, wall mounting bracket and AAA battery

## 445713 Additional Features

- Dual indoor/outdoor Temperature and Humidity displays
- Remote “outside” sensor on 35” (89cm) cable

## 445715 Additional Features

- Remote sensor on 35” (89 cm) cable
- User accessible temperature and humidity calibration adjustments
- Available with a NIST traceable certification
- Optional RH calibration bottles

CE

Specifications:	445703	445713	445715
Humidity range	10 to 99%RH	10 to 99% RH	10 to 99% RH
Basic RH accuracy	± 5% (25 to 85%)	± 5% (25 to 85%)	± 4% (25 to 85%)
Temperature range	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)
Basic Temperature Accuracy	±1.8°F/1°C (14 to 122°F)	±1.8°F/1°C (14 to 122°F)	±1.8°F/1°C (14 to 122°F)
Dimensions	4.3x3.9x0.78”(109x99x20mm)		
Weight	6 oz (169g)		

445580-C Optional calibration salt bottles for 445715



445713 Big Digit Indoor/Outdoor Hygro-Thermometer

445703 Big Digit Hygro-Thermometer



445715 Big Digit Remote Probe Hygro-Thermometer

## Ordering Information:

- 445703** .....Big Digit Hygro-Thermometer
- 445713** .....Big Digit Indoor/Outdoor Hygro-Thermometer
- 445715** .....Big Digit Remote Probe Hygro-Thermometer
- 445715-NIST** ..Big Digit Remote Probe Hygro-Thermometer with NIST certificate
- 445580-C** .....Optional 33% and 75% RH calibration bottles for 445715